

Features:

- Available with LED or MR16 halogen lamps.¹
- Precision machined from aluminum or brass with all stainless steel hardware.
- Removable cap available in four cutoff styles.
- Each cap holds up to three lens accessories.
- Flush lens and weep hole (in regressed caps), reduces water pooling, keeping the lens cleaner, longer.
- Thick walled cap and optimized high temperature silicone O-ring placement prevents leaking.
- Large cap set screw prevents stripping.
- 1/2" NPS mount thread allows for use on industry standard mounts.
- CSA tested & certified to US & Canadian safety standards for use in wet locations.

1. Available lamp wattage varies by material and mounting method.



Photo: FL16A with BN finish and C1F cap, mounted on an MO14 stake mount.

Model **FL16**

Low Voltage
MR16 Halogen (42W)
LED (2W)



- Ø2 3/8" body, 5 7/16" maximum body length.
- Aluminum and brass.
- Remote transformer required.

Accessories:



Lenses & Baffles
(Model AC3)



Adjustable Cutoff Shrouds
(Models AC4 & AC5)



Machined Stems
(Model AC1)



Electronic Transformer
(Model XM3)



Magnetic Transformer
(Model XM2)

Mounts:



In-grade Stake
(Models MO1, MO2, & MO14)



In-grade Housing
(Models MO11)



Wall Canopies
(Models MO3, MO4, & MO15)



Cast Box & Covers
(Models MO5 & MO6)