



Photos: above: PA1B with AGE finish, mounted on an MO1 Junction Mount.
inset: PA2S with NAT finish, mounted on an MO1 Surface Mount.

Features:

- Available with T4 halogen lamp.
- Precision machined from aluminum, brass, or stainless steel with all stainless steel hardware.
- Frosted radial lens creates a smooth, even distribution of light.
- High temperature silicone O-rings create a water tight fixture.
- Standard fixed stem lengths from 6" to 48", in increments of 6", covers most applications, while the adjustable stem options give infinite control of fixture height.
- Standard surface mounts, stake and junction mounts, and integral transformer mounts allow for use in virtually any installation.
- CSA tested & certified to US & Canadian safety standards for use in wet locations.



Model **PA1**
Low Voltage
T4 Halogen (35W)



- Ø6" shade, Ø1" stem.
- Aluminum, brass, and stainless steel.
- Remote transformer required.

Model **PA2**
Low Voltage
T4 Halogen (35W)



- Ø1" head, Ø1" stem.
- Aluminum, brass, and stainless steel.
- Remote transformer required.

• See page 31 for PA1 and PA2 photometry information.

Accessories:



Machined Stems
(Model AC1)



Electronic Transformer
(Model XM3)



Magnetic Transformer
(Model XM2)

Mounts:



In-grade Stake
(Models MO1 & MO14)