

### Installation Instructions

#### INSTRUCTIONS PERTAINING TO A RISK OF FIRE, OR INJURY TO PERSONS. IMPORTANT SAFETY INSTRUCTIONS. SAVE THESE INSTRUCTIONS

#### Warning! To reduce the risk of FIRE OR INJURY TO PERSONS:

1. Do not touch luminaire while lamp is on. Turn off/unplug and allow to cool before replacing lamp.
2. Lamp gets HOT quickly! Contact only switch/plug when turning on. Do not touch hot lens, faceplate, or cover.
3. Keep lamp away from materials that may burn.
4. Do not touch lamp at any time. Use a soft cloth. Oil from your skin may damage lamp.
5. Do not operate the luminaire with damaged or missing parts.
6. Do not disassemble luminaire beyond cover/faceplate removal to facilitate lamp and/or accessory installation or replacement.
7. Remove any debris accumulated in the cap, and/or clean lens periodically.
8. Do not install luminaire within 10 feet of a pool, spa, or fountain.
9. Have fixture installed in accordance with all applicable installation codes and standards by a person familiar with the construction and operation of the fixture and the hazards involved.
10. Consult a qualified electrician to ensure correct branch circuit conductor. **NOTE: Supply conductors in box must be rated for at least 105°C.**

#### Installation

1. Loosen the Cover Set Screws (3X) with a 3/32" hex tool (do not remove screws) and remove the Cover Assembly from the Faceplate.
2. Loosen the Faceplate Screws (2X) with a 1/8" Hex tool and remove the Faceplate Assembly from the Box Assembly. Note: The Socket Mount Assembly will be attached to the Faceplate Assembly.
3. Mount the Box Assembly in the wall, per applicable building codes, so that the front face of the box is flush with the wall. Note: This fixture is not intended for use with combustible surfaces or thermal insulation contact.
4. Run conduit and appropriate supply conductors to the Box Assembly, per applicable standards. Note: Supply conductors in box must be rated for at least 105°C.
5. Connect the socket leads to the supply conductors using the appropriate connectors per applicable codes (make sure socket leads pass through center opening in the Box Gasket). Note: Be sure rating on the luminaire Label matches the power being supplied.
6. If required, install lamp and accessories as described below.
7. Slip the Box Gasket over the Cap until it is flush with the back of the faceplate. Align the Box Gasket holes with the Faceplate holes.
8. Insert the Faceplate Assembly in to the Box Assembly until the Faceplate meets the wall and the Box Gasket is uniformly compressed. Note: Make sure the wiring is not kinked or pinched in any way.
9. Use the Faceplate Screws (2X) to attach the Faceplate Assembly to the Box Assembly. Note: Make sure Faceplate is flush with wall, and the gasket is not pinched.
10. Slide the Cover Assembly over the Faceplate as far as it will go, and properly orient. Note: Eyelid should not be pointed up as it will fill with water and debris.
11. Gently tighten each Cover Set Screw against Faceplate.
12. Once the Cover Set Screws are all contacting the Faceplate, firmly tighten all three Cover Set Screws. Note: Make sure the Cover is tightened on to the Faceplate with all three Cover Set Screws; otherwise, the cover may loosen.

#### Lamp Maintenance

1. Remove power from fixture and let cool before touching. Caution! Luminaire may still be hot!
2. Remove the Cover & Faceplate Assemblies as described in 'Installation' above.
3. Loosen the Cap Set Screw using a 3/32" hex tool – do not remove screw!
4. Remove the Socket Mount Assembly from the Cap.
5. Pull lamp straight out of Socket. Caution! Lamp may still be hot! Be sure lamp has cooled before touching.
6. Inspect Socket for any damage.

