

METALWORKS™ – Standard

Vector™

smooth texture

METALWORKS
Unperforated

METALWORKS Vector (Extra Microperforated) Gun Metal Grey with PRELUDE® 15/16" Exposed Tee grid

Removal



Step 1:
Locate the access kerf by pushing on the panel edges until the panel moves.



Step 2:
Push on the access kerf edge until it clears the grid flange.



Step 3:
Lower the kerfed edge of the panel and locate the security clip.




Step 4:
Hold the panel with one hand while pushing the security clip away from the cross tee.




Step 5:
Slide the panel back and down to remove it from the grid module.

Detail



METALWORKS
Vector
Microperforated



METALWORKS Vector
Extra Microperforated



METALWORKS Vector
Unperforated with
PRELUDE 15/16"
Exposed Tee grid

Color Selection



White (WH)



Silver Grey (SG)



Gun Metal
Grey (MY)

Due to printing limitations,
shade may vary from actual product.



METALWORKS Vector Faceted
Applications (no clip required)

For more information about faceted applications, refer to CS-3701 and installation instructions on our web site at armstrong.com/metalworks, search keyword (example: faceted).



METALWORKS™ – Standard

Vector™

smooth texture

Recycled Content: 25%

Key Selection Attributes

- Patented ceiling installs on new or existing 15/16" exposed tee grid resulting in a thin 1/4" reveal
- Cutouts for recessed lights and sprinklers available
- Custom colors and perforations available as premium options
- Durable
 - Scrubbable
 - Soil-resistant
 - Washable
- Good NRC with acoustical fleece (perforated panels)
- Installs with minimal plenum clearance
- 100% downward accessible, without tools

Typical Applications




- Lobbies and corridors
- Office and healthcare
- Hospitality and retail
- Transportation
- Wherever plenum depth is limited
- High access areas
- Exterior applications – refer to METALWORKS Vector for Exterior Applications data page CS-3298

Colors

White (WH)
Silver Grey (SG)
Gun Metal Grey (MY)

Visual Selection

Performance Selection

Grid Face	Edge Profile	Item * Number	Dimensions	Acoustics		Factory Mutual Certified Flame Spread/ Smoke Developed	Light Reflect	Durable			
				NRC	CAC						
METALWORKS Vector † Unperforated											
15/16"	Vector	9418U6A1__	2' x 2'		0.10	36	25-50	0.77	Scrub	Soil	Wash
											
METALWORKS Vector † Microperforated (with acoustical fleece)											
15/16"	Vector	9420U6A2__	2' x 2'		0.65 0.90**	31*	25-50	0.61	Scrub	Soil	Wash
											
METALWORKS Vector † Extra Microperforated (with acoustical fleece)											
15/16"	Vector	2118U6A2__	2' x 2'		0.65 0.90**	33*	25-50	0.77	Scrub	Soil	Wash
											

* With optional field-cut #747 mineral fiber backing

** NRC 0.90 with optional fiberglass infill (#8200100)

† U.S. Patent 5,417,025; 5,253,463; 5,355,646

◆ When specifying or ordering, include the appropriate color suffix (WH, SG or MY) with the item number. Light reflectance is for white only.

Accessories

Item Number	Dimensions	Color	Substrate
METALWORKS Vector - FIBERGLASS INFILL PANEL			
8200100	2' x 2' x 1"	Black	Poly-wrapped Fiberglass

SPECIAL ORDER

METALWORKS Vector - SINGLE-SLOT AIR DIFFUSER			
84008__	2' x 2'	White Silver Grey Gun Metal Grey	Cold-rolled Steel



METALWORKS
Single-Slot Air Diffuser
(Gun Metal Grey)

Physical Data

Material

Electrogalvanized Steel – .021" thickness

Surface Finish

Factory-applied powder-coated finish (post-coated)

Fire Certification

Factory Mutual Approvals
Specification tested per ASTM E 84 and CAN/ULC S102

ASTM E 1264 Classification

Fire Class – Class A
9418U6A1__ – Type XX (Unperforated steel ceiling panel) Pattern G
2118U6A2__, 9420U6A2__ – Type XX (Microperforated steel ceiling panel) Pattern C

Backloading Recommendation

Contact TechLine for specific information

Weight; Square Feet/Carton

See product details at armstrong.com/ceilings

Warranty

1-year limited warranty. See warranty details at armstrong.com/ceilings

Application Considerations

Not intended for kitchen/food preparation or clean room applications

Recommended Suspension System

Items	Suspension System	Faceted
2118U6A2__, 9418U6A1__, 9420U6A2__	15/16" PRELUDE® XL	compatible

For faceted applications, see armstrong.com for further information.

TechLine™ / 1 877 ARMSTRONG
1 877 276 7876

armstrong.com/metalworks

CS-3270-207

© AWI Licensing Company, 2007 • Printed in the United States of America • 10% post consumer waste. Printed with vegetable inks.  Recyclable.