

Cabinet M336-15 Conservation Cabinet





Cabinet Specifications



Conservation Cabinet

Features:

- Construction-solid heavy-gauge steel, reinforced welded for safe stacking
 Top-WaterShieldtm cap top provides umbrella type protection for cabinet contents
- Door-lift-off hinges (door easily removed for ease of transfering specimens), recessed handle, and label holder
- Sealing-door seals with closed cell Elastomeric Sealtm and three-point latching system
- Hardware-heavy bright nickel-plated for long lasting protection.
- Powder coating museum quality Epoxy Polyester powder coating, non off-gassing
- Six Sturdy, full-width shelves
- Cabinet will accommodate additional full width drawers and shelves (standard and heavy duty) with 1" adjustment
 - Drawers (20) 1 1/2" drawers or (16) 3 1/2" drawers
 - Shelves (18) standard or (9) heavy duty, 1 1/2" and 3 1/2" drawers and shelves

Optional Features:

- Visual Lift Off Doors with silicone grommet seal and laminated safety glass
 Level-Easetm swivel levelers accessible from inside the cabinet
- Vent with sliding closure plate
- Nickel-plated filter pocket that mounts behind vent
- Magnetic fumigant pocket
- Recessed handle locks

Cabinet Weight and Drawer Specifications:

- Cabinet, 235 lbs.
- 1 1/2" drawers full width, 8 lbs., 34 1/4" wide x 13 1/2" deep x 1 1/2" high
- 3 1/2" drawers full width, 9 lbs., inside 34 1/4" wide x 13 1/2" deep x 3 1/2" high
- Drawer capacity 100 lbs. evenly distributed
- Shelf capacity standard, 300 lbs. evenly distributed; heavy duty, 1000 lbs. evenly distributed

Capacity

Dimensions

39 1/2"

16 5/8"

84"

Width:

Depth:

Height:

23.7 cubic feet of storage space

Materials:

All materials used in the fabrication, finishing, and assembly of all cabinets and accessories have been tested. They have been certified to be safe and non off-gassing.

Testing:

Cabinet construction and seals have been tested for retention by an independent testing laboratory. Test results are available, upon request.

Warranty:

All cabinets and accessories are guaranteed to be free from defects in material and workmanship for a period of five years.



