



DUAL CONTROL KITCHEN FAUCET WITH PULL-DOWN SPRAY AND SOAP DISPENSER

MODEL NUMBER: ☐ 4464F Pull Down Kitchen Faucet with Soap Dispenser Finish (Chrome) 392mm 195mm (15-3/8)(7-11/16)215mm (8-7/16) 75mm (2-15/16) 35mm 28mm 28mm (1-3/8)DIA (1-1/8) DIA. (1-1/8) DIA. MOUNTING HOLES (4) 89mm 35mm -(1-3/8)(3-1/2)FLEXIBLE **FLEXIBLE** MAX HOSE HOSE FOR GROUND JOINT 152mm - 305mm (6 TO 12) FLEXIBLE OR 1/2" O.D. SLIP CONNECTION

GENERAL DESCRIPTION:

Durable construction and metal lever handles. Cast brass valve bodies with flexible hose connections for 6" to 12" (152mm to 305mm) installations. One-half inch male inlet shanks with brass coupling nuts. 1/4 turn washerless ceramic disc valve cartridges. 2.2gpm / 8.3 L/min maximum flow rate. With soap dispenser.

PRODUCT FEATURES:

Brass Construction: Ideal for prolonged contact with water. Ceramic Disc Valve Cartridges: Assure a lifetime of

smooth handle operation and drip-free performance.

Low Lead: Meets NSF Standard 61/Section 9 & Prop 65 lead requirements.

Pull-down Spray: Adjustable spray pattern-stream to spray.

Integral Check Valves: Prevents back flow.

Finish: Polished Chrome

SUGGESTED SPECIFICATION:

Dual control kitchen faucet shall feature durable construction with pull-down spray. Faucet shall feature brass spout and cast brass valve bodies with flexible hose connections for 6" to 12" installations. Shall feature 1/4 turn washerless ceramic disc valve cartridges. With soap dispenser. Fitting shall be American Standard Model # 4464F.




WYNSTON™

DUAL CONTROL KITCHEN FAUCET WITH PULL-DOWN SPRAY AND SOAP DISPENSER

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ANSI A117.1 ASME A112.18.1 NSF 61/Section 9 CSA B125



		Finish Options
Product		Polished Chrome
Number	Description	002
4464F	Pull-down Kitchen Faucet with Soap Dispenser.	

Meets the American Disabilities Act Guidelines and ANSI A117.1 Requirements for the physically challenged.