

# **Shiloh**<sup>TM</sup>

31731

Elongated Front, 12" [305 mm] Rough-in, One-Piece Toilet



#### **Features**

- Low Water Consumption 1.6 gpf / 6.0 lpf
- Powerful HemiFlush™ Flushing Technology
- Ideal for Banjo Top Installations
- High Volume 3" [76 mm] Flush Valve
- Pilot Fill Valve
- Includes Heavy-Duty, EasyClose™ Toilet Seat
- Large Water Surface Area
- 12" [305 mm] Rough-in
- 2" [51 mm] Fully Glazed Trapway
- Side Mount, Left Hand, Polished Chrome, Metal, Trip Lever
- Available in White, Bone and Biscuit
- Limited Lifetime Warranty



### Model #

### Description

31731

Elongated front, one-piece toilet combination with 3" [76 mm] flush valve and pilot fill valve. 12" [305 mm] rough-in. Includes side mount, left hand, polished chrome, metal, trip lever and EasyClose<sup>m</sup> toilet seat. Less supply.





*Shiloh*<sup>™</sup> 31731

### Specifications

Water Pressure Range: 20 to 80 P.S.I.

*Flush System:* HemiFlush<sup>™</sup> Flushing Technology

Water Usage: 1.6 gpf/6.0 lpf Water Surface Area: 10-1/4" x 9"

[260 mm x 229mm]

Trap Diameter: 2" [51 mm]
Water Seal: 2-3/8" [60 mm]
Shipping Cubes: 5.7 ft<sup>3</sup> [.16 m<sup>3</sup>]
Shipping Weight: 85 lbs. [39 kg]

**Warranty**: Vitreous China - Limited Lifetime Tank Trim - Limited One Year %" [16mm] 20" [508mm] -8%" [206mm] 18%" [479mm] -6" [152mm] 10% 5½" [152mm] [257mm] [140mm] BOTTOM VIEW OF FOOT 4½" [114mm] - FINISHED WALL 30¼" [768mm] 16%" [416mm] [651mm] 14½" [368mm] INISHED [203mm] 4½" [114mm] 3/8" [10mm] N.P.S. SUPPLY C/L OF OUTLET

IMPORTANT: These dimensions are nominal and may vary within the range of tolerances established by ASME Standard A112.19.2

## Features and Upgrades



P030187

Features a patented flow regulator, debris filter and positive shut-off for added functionality. Operates at both low and high water pressure and can be adjusted to achieve optimum performance.



P030398-068 Left hand, Polished Chrome [068],

metal trip lever.



P030743

Designed for maximum performance this 3" [76 mm] flush valve features high volume flow rate for a quick and quiet flush. Nearly doubling the potential flow rate of a standard 2" [51 mm] flush valve.



8096

White, EasyClose™ toilet seat. Constructed of durable high-imapct plastic and closes slowly and quietly with a gentle touch.

P030284 Flapper

Customer Service United States
41 Cairns Road
Mansfield, OH 44903
Email: customerservice@craneplumbing.com

Customer Service Canada 15 Crane Ave. Stratford, ON N5A 6T3 Email: sales@craneplumbing.ca

www.craneplumbing.ca

www.craneplumbing.com www.cran

