

Eco Saratoga™

31972

Round Front, Gravity Force, **Dual Flush**, 12" [305 mm] Rough-in, Two-Piece Toilet



Features

- Environmentally Friendly
- High Efficiency 1.1 gpf / 4.0 lpf or 1.6 gpf / 6.0 lpf
- Qualifies for One [1] LEED Point
- G^{2 ™} Gravity force, Dual Flush Flushing Technology
- Tower Style Flapperless Flush Valve
- Pilot Operated Fill Valve
- Large Water Surface Area
- 12" [305 mm] Rough-in
- 2" [51 mm] Fully Glazed Trapway
- Top Mount, Polished Chrome, Dual, Push Button Actuator
- Sanitary Bar for Easy Cleaning
- Available in White, Bone and Biscuit
- Limited Lifetime Warranty



Model #	Description
31972	Round front, two-piece, gravity force, dual flush toilet combination, 12" [305 mm] rough-in. Includes tank trim and top mount, polished chrome, dual, push button actuator. Less toilet seat and supply.
3352 31964	Round front toilet bowl only.12" [305 mm] rough-in. Less toilet seat. Gravity force, dual flush tank and cover only with tank trim and top mount, polished chrome, dual, push button actuator. Less supply.

Optional Toilet Seat

8085 Round, "Lift 'N' Clean", heavy-duty plastic, toilet seat











ApprovedLos Angeles Department of
Water and Power

The Green Building / LEED programs was created to provide contractors, building engineers, developers and architects with incentives or rewards for utilizing energy saving and water conservation products in the construction or renovation of their buildings. The LEED program provides points or credits that can be used to offset elements of the construction that would be debits against the property. Using a 1.6 gpf / 6.0 lpf toilets as the baseline, a HET toilet or HEU urinal that has a minimum average water savings of 20% can earn one [1] LEED point, or a minimum water savings of 32% can earn two [2] LEED points.

Eco Saratoga™

Specifications

Water Pressure Range: 20 to 80 P.S.I. Flush System: $G^{2^{TM}}$ Flushing Technology Water Usage: 1.1 gpf/4.0 lpf or 1.6 gpf/6.0 lpf

Water Surface Area: 9" x 7"

[227 mm x 178 mm]

Trap Diameter: 2" [51 mm] **Water Seal:** 2-5/8" [60 mm]

Shipping Cubes:


3352 Bowl: 2.9 ft³ [.08 m³] 31964 Tank: 1.7 ft³ [.05 m³]

Shipping Weight:

3352 Bowl: 41 lbs. [19 kg] 31964 Tank: 36 lbs. [16 kg]

Warranty:

Vitreous China - Limited Lifetime Tank Trim - Limited One Year



IMPORTANT: These dimensions are nominal and may vary within the range of tolerances established by ASME Standard A112.19.2

Features and Upgrades



P030176 Pilot operated fill valve



P030730 Dual, steel wire-driven flush valve



P030328
Dual action push button
Available in Polished Chrome finish only.



8085 Round "Lift 'N' Clean" toilet seat Seat can be removed quickly for ease of cleaning.

Customer Service United States
41 Cairns Road
Mansfield, OH 44903
Email: customerservice@craneplumbing.com

Customer Service Canada 15 Crane Ave. Stratford, ON N5A 6T3 Email: sales@craneplumbing.ca

