

**SPECIFICATIONS FOR COMMUNITY
CONGRESS BOOKCASE COLLECTION**
**MODELS: CO3630BC – CO3636BC – CO3648BC – CO3660BC –
CO3672BC – CO3684BC**

Wood: All exposed parts are constructed of multiple layered plywood with oak veneer. All surfaces are well-sanded and free from brashness, discoloration, worm holes, pits and shakes.

Details of Construction:

All shelves and side panels are fabricated from ¾" thick, 7-ply hardwood plywood. Back panels are constructed from ¼" thick plywood. The top and bottom shelves use groove and tenon joinery. Joints are secured with wood glue and by screws through the wood cleats which are concealed under the shelves. The back panel fits precisely into grooves in the side panels, and is glued, screwed and pinned to the cabinet. Hardwood corner blocks are securely glued and screwed to the cabinet beneath the bottom shelf for added support. The interior shelf (multiple shelves on high units) is movable and adjustable to accommodate books, binders, etc. of almost any standard size. Units 60" and taller are constructed with a fixed middle shelf which add strength and stability. The adjustable shelves are pinned solidly during shipment to prevent damage. All units are equipped with adjustable glides.

Finish: Each cabinet begins the finish process with an even coat of a no-wipe stain. A coat of catalyzed sealer is applied and oven dried for 30 minutes. Next, a light sanding is given to the sealer to assure a smooth finish. Then the product is sprayed with a 45 sheen catalyzed lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

Warranty: All bookcases are covered by a full 5-year warranty against any defects in materials and/or workmanship.

Dimensions:

	CO3630BC	CO3636BC	CO3648BC	CO3660BC	CO3672BC	CO3684BC
W	36"	36"	36"	36"	36"	36"
D	12"	12"	12"	12"	12"	12"
H	30"	36"	48"	60"	72"	84"