


SAMPLE CATALOG NUMBER
 CB5114 - 2LF13(MVOLT) - AG7038 - BCA - XPS
 Model Number Lamping Option (Voltage) Bracket Finish Accent Bar Finish Option


Model				Lamping Options	Finish			Options
Model Number	Dimensions			Bracket	Accent Bar	Accent Bar and Medallion		
CB5110 	W	4-3/4"	(121 mm)	2LF13 2N40	PTD	PTD	• CB BA PB BB • SN BCA SNA • BCB	• ABA DCC REM XEM XPS
	H	17"	(432 mm)					
	D	4"	(102 mm)					
	MC	8-1/2"	(216 mm)					
CB5112 	W	4-3/4"	(121 mm)	2LF13 2N40	PTD	PTD	• CB BA PB BB • SN BCA SNA • BCB	• ABA DCC REM XEM XPS
	H	17"	(432 mm)					
	D	4"	(102 mm)					
	MC	8-1/2"	(216 mm)					
CB5114 	W	4-3/4"	(121 mm)	2LF13 2N40	PTD	PTD	• BCB BA • CB BB SNA BCA	• ABA DCC REM XEM XPS
	H	17"	(432 mm)					
	D	4"	(102 mm)					
	MC	8-1/2"	(216 mm)					
CB5116 	W	4-3/4"	(121 mm)	2LF13 2N40	PTD	PTD	• CB BA PB BB • SN BCA SNA • BCB	• ABA DCC REM XEM XPS
	H	17"	(432 mm)					
	D	4"	(102 mm)					
	MC	8-1/2"	(216 mm)					

LINE DRAWINGS


CB5110




CB5112



CB5114



CB5116



ABBREVIATION KEY

• Indicated Finish or Option is not available with XPS

Dimensions

- W** Width
- H** Height
- D** Depth (measured from wall to front of fixture)
- MC** Mounting Center (measured from top of fixture to center of junction box)

Lamping Options (Voltage)

- LF13** 13w twin tube, 4-pin 2GX7 base, FLR (MVOLT)
 - N40** 40w T-6.5, intermed base, INC (120V)
- MVOLT is a ballast that operates 120V through 277V

Finishes (see inside back cover)

- PTD** Painted - specify color code (ex. BRNZ for Bronze)
- BA** Brushed Aluminum
- BB** Brushed Brass
- BCA** Brushed Chrome Alternative
- **BCB** Brushed Chrome
- **CB** Polished Chrome
- **PB** Polished Brass
- **SN** Satin Nickel
- SNA** Satin Nickel Alternative

Options

- **ABA** Hand Painted Alabaster Alternative
- DCC** Damp clear coat required for all metal finishes in damp locations
- REM** Remote emergency battery pack for fluorescent lamping
- XEM** Emergency battery pack mounted in provided recessed box for fluorescent lamping (replaces standard junction box)
- XPS** Express 10 day shipment

PHOTOMETRICS and BIM


Complete BIM (Building Information Modeling) and photometric files for these models may be downloaded from www.visalighting.com

Reports

IES File Number	LER	Report	page
CB5110-LF13	45	02585	408
CB5112-LF13	45	02585	408
CB5114-LF13	45	02585	408
CB5116-LF13	45	02585	408

See report on indicated page for complete detail

Candela Distribution



Door Height = 7'
 Ceiling Height = 9'
 Silhouette Height = 6'

COLONNADE™

INDOOR

DECORATIVE AND PERFORMANCE

WALL



CB5110-TW9016-PB



CB5112-GW9002-GW9002



CB5114-AG7038-BCA



CB5116-TG7042-CB

FEATURES

- 5 year product warranty
- ADA compliant
- Solid metal bar trim
- Die-cast center bracket
- Oven cured no VOC acrylic powder coat for painted finishes; oven cured low VOC clear coat on metal finishes
- Extruded 1/8" thick white acrylic diffuser standard with matte finish, UV stable, UL-94 HB flame class rated
- Easy tool-less relamping
- Fluorescent or incandescent lamping
- High power factor electronic ballast (fluorescent lamping)
- Mounts to standard electrical junction boxes (by others) with provided hardware

COMPANIONS



SUGGESTED VARIATIONS

- Specialty finishes to match architectural detail
- Add roll bars or rearrange roll bar locations
- Fluorescent lamping up to (2) 18w TT with increased fixture height
- Fused circuit protection
- Can be constructed of non-ferrous materials for use in magnetic resonance imaging (MRI) rooms



Approved for indoor damp locations.
Metal finishes require DCC (damp clear coat) for 5 year warranty