





**SAMPLE CATALOG NUMBER**

CB3660 - 1F27(MVOLT) - CW9001 - XPS  
 Model Number Lamping Option (Voltage) Finish Option


Model				Lamping Options	Finish	Options
Model Number	Dimensions					
<b>CB3660</b> 	W	8-7/8"	(225 mm)	<b>1F18</b>	<b>PTD</b>	<b>REM</b> <b>XEM</b> <b>XPS</b>
	H	16"	(406 mm)	<b>1F27</b>		
	D	4"	(102 mm)	<b>2N60</b>		
	MC	8"	(203 mm)			
<b>CB3662</b> 	W	7-3/4"	(197 mm)	<b>1F18</b>	<b>PTD</b>	<b>REM</b> <b>XEM</b> <b>XPS</b>
	H	16"	(406 mm)	<b>1F27</b>		
	D	4"	(102 mm)	<b>2N60</b>		
	MC	8"	(203 mm)			
<b>CB3664</b> 	W	7"	(178 mm)	<b>1F18</b>	<b>PTD</b>	<b>REM</b> <b>XEM</b> <b>XPS</b>
	H	16"	(406 mm)	<b>1F27</b>		
	D	4"	(102 mm)	<b>2N60</b>		
	MC	8"	(203 mm)			

**LINE DRAWINGS**

**CB3660**



**CB3662**



**CB3664**



**ABBREVIATION KEY**

**Dimensions**

- W** Width
- H** Height
- D** Depth (measured from wall to front of fixture)
- MC** Mounting Center (measured from top of fixture to center of junction box)

**Lamping Options (Voltage)**

- F18** 18w long twin tube, 2G11 base, FLR (MVOLT)
  - F27** 27w long twin tube, 2G11 base, FLR (MVOLT; 347V)
  - N60** 60w A-19, medium base, INC (120V)
- Specify Voltage or MVOLT  
 MVOLT is a ballast that operates 120V through 277V

**Finishes (see inside back cover)**

- PTD** Painted - specify color code (ex. BRNZ for Bronze)

**Options**

- REM** Remote emergency battery pack for fluorescent lamping
- XEM** Emergency battery pack mounted in provided recessed box for fluorescent lamping (replaces standard junction box)
- XPS** Express 10 day shipment

**BIM**

Complete BIM (Building Information Modeling) for these models may be downloaded from [www.visalighting.com](http://www.visalighting.com)

Door Height = 7'  
 Ceiling Height = 9'  
 Silhouette Height = 6'



CB3660-CW9001



CB3662-BSIL




CB3664-PB1035

## FEATURES

- 5 year product warranty
- ADA compliant
- Heavy gauge fabricated metal housing
- Oven cured no VOC acrylic powder coat for painted finishes
- Front shield features snap lock for easy tool-less relamping
- Fluorescent or incandescent lamping
- High power factor electronic ballast (fluorescent lamping)
- Mounts to standard electrical junction box (by others) with provided hardware. XEM option requires replacement of junction box with proprietary junction box (included with XEM option). The XEM junction box is available as a ship-ahead component for rough-in if needed

## COMPANIONS



## SUGGESTED VARIATIONS

- Specialty finishes to match architectural detail
- Custom window cutout in housing
- Increase or decrease housing height and/or width
- Fluorescent lamping T-5/HO with increased housing height
- Fused circuit protection
- Can be constructed of non-ferrous materials for use in magnetic resonance imaging (MRI) rooms



Approved for indoor damp locations.  
Metal finishes require DCC (damp clear coat) for 5 year warranty