


SAMPLE CATALOG NUMBER						
CB3456	-	1F27(MVOLT)	-	SNA	-	XPS
Model Number		Lamping Option (Voltage)		Finish		Option

Model		Lamping Options		Finish		Options	
Model Number	Dimensions						
<b>CB3456</b>	W	22-7/8"	(581 mm)	<b>1F27</b> <b>2QF26</b> <b>2N60</b>	<b>PTD</b>	• <b>CB</b>	• <b>ABA</b> <b>FUSE</b>
	H	7-1/2"	(191 mm)		<b>BA</b>	<b>PB</b>	<b>DCC</b> <b>REM</b>
	D	11-3/8"	(289 mm)		<b>BB</b>	• <b>SN</b>	• <b>DIM-A</b> <b>XEM</b>
	MC	2-3/4"	(70 mm)		<b>BCA</b>	<b>SNA</b>	• <b>DIM-L</b> <b>XPS</b>
					• <b>BCB</b>		

LINE DRAWINGS

**CB3456**



ABBREVIATION KEY

• Indicated Finish or Option is not available with XPS

Dimensions

- W** Width
- H** Height
- D** Depth (measured from wall to front of fixture)
- MC** Mounting Center (measured from top of fixture to center of junction box)

Lamping Options (Voltage)

- F27** 27w long twin tube, 2G11 base, FLR (MVOLT; 347V)
  - QF26** 26w quad, 4-pin G24q-3 base, FLR (MVOLT; 347V)
  - N60** 60w A-19, medium base, INC (120V)
- Specify Voltage or MVOLT  
MVOLT is a ballast that operates 120V through 277V

Finishes (see inside back cover)

- PTD** Painted - specify color code (ex. **BRNZ** for Bronze)
- BA** Brushed Aluminum
- BB** Brushed Brass
- BCA** Brushed Chrome Alternative
- **BCB** Brushed Chrome
- **CB** Polished Chrome
- PB** Polished Brass
- **SN** Satin Nickel
- SNA** Satin Nickel Alternative

Options

- **ABA** Hand Painted Alabaster Alternative
- DCC** Damp clear coat required for all metal finishes in damp locations
- **DIM-A** Fluorescent dimming, Advance Mark 10, specify voltage (QF26 lamping only)
- **DIM-L** Fluorescent dimming, Compact SE, specify voltage (QF26 lamping only)
- FUSE** Fusing
- REM** Remote emergency battery pack for fluorescent lamping
- XEM** Emergency battery pack mounted in provided recessed box for fluorescent lamping (replaces standard junction box)
- XPS** Express 10 day shipment

BIM

Complete BIM (Building Information Modeling) for these models may be downloaded from [www.visalighting.com](http://www.visalighting.com)

Door Height = 7'  
Ceiling Height = 9'  
Silhouette Height = 6'

**CONE™**

INDOOR

DECORATIVE AND PERFORMANCE

WALL



CB3456-SNA

**FEATURES**

- 5 year product warranty
- Heavy gauge spun trim rings
- Thermally formed 1/8" thick white acrylic diffuser standard with matte finish, UV stable, UL-94 HB flame class rated
- Oven cured no VOC acrylic powder coat for painted finishes; oven cured low VOC clear coat on metal finishes
- Easy tool-less relamping
- Fluorescent or incandescent lamping
- High power factor electronic ballast (fluorescent lamping)
- Mounts to standard electrical junction box (by others) with provided hardware. XEM option requires replacement of junction box with proprietary junction box (included with XEM option). The XEM junction box is available as a ship-ahead component for rough-in if needed

**COMPANIONS**



**SUGGESTED VARIATIONS**

- Mix and match accents and trim from other product designs
- Can be constructed of non-ferrous materials for use in magnetic resonance imaging (MRI) rooms
- Larger diffuser sizes available



Approved for indoor damp locations.  
Metal finishes require DCC (damp clear coat) for 5 year warranty