






SAMPLE CATALOG NUMBER

OW1304 - 2F39(MVOLT) - GLIM - GLIM - XPS
 Model Number Lamp (Voltage) Frame Finish Accent Bar and End Cap Finish Option


Model				Lamping Options	Finish		Options
Model Number	Dimensions				Frame	Accent Bar and End Cap	
OW1300 	L	18-1/4"	(464 mm)	1F39 2N40T10	PTD	PTD	FUZE HM REM XPS
	D	4"	(102 mm)				
	MC	9-1/8"	(232 mm)				
OW1302 	L	24-1/4"	(616 mm)	1F40 1F50 2FS14 2N40T10	PTD	PTD BSS PSS	FUZE HM REM XPS
	D	4"	(102 mm)				
	MC	12-1/8"	(308 mm)				
OW1304 	L	36"	(914 mm)	2F39 2FS21	PTD	PTD BSS PSS	FUZE HM REM XPS
	D	4"	(102 mm)				
	MC	18"	(457 mm)				
OW1306 	L	47-3/4"	(1527 mm)	2F40 2F50 2FS28	PTD	PTD BSS PSS	FUZE HM REM XPS
	D	4"	(102 mm)				
	MC	23-7/8"	(606 mm)				

LINE DRAWINGS


OW1300




OW1302



OW1304



OW1306



ABBREVIATION KEY

Dimensions

- L Length
- D Depth (measured from wall to front of fixture)
- MC Mounting Center (measured from top of fixture to center of junction box)

Lamping Options (Voltage)

- F39 39w long twin tube, 2G11 base, FLR (MVOLT; 347V)
- F40 40w long twin tube, 2G11 base, FLR (MVOLT)
- F50 50w long twin tube, 2G11 base, FLR (MVOLT; 347V)
- FS14 14w T-5, mini bi-pin base, FLR (MVOLT; 347V)
- FS21 21w T-5, mini bi-pin base, FLR (MVOLT; 347V)
- FS28 28w T-5, mini bi-pin base, FLR (MVOLT; 347V)
- N40T10 40w T-10, medium base, INC (120V)

Specify Voltage or MVOLT
 MVOLT is a ballast that operates 120V through 277V

Finishes (see inside back cover)

- PTD Painted - specify color code (ex. BRNZ for Bronze)
- BSS Brushed stainless steel
- PSS Polished stainless steel

Options

- FUZE Fusing
- HM Horizontal mount (vertical is standard)
- REM Remote emergency battery pack for fluorescent lampping (rated for dry location, 32° F / 0° C minimum)
- XPS Express 10 day shipping

PHOTOMETRICS and BIM


Complete BIM (Building Information Modeling) and photometric files for these models may be downloaded from www.visalighting.com

Reports

IES File Number	LER	Report	page
OW1300-1F39			37
OW1302-1F40	39	03790	409
OW1304-2F39			37
OW1306-2F40			37

See report on indicated page for complete detail

Candela Distribution



Door Height = 7'
 Ceiling Height = 9'
 Silhouette Height = 6'

