


SAMPLE CATALOG NUMBER

OW1724 - 1TF32(MVOLT) - TG7042 - XPS
 Model Number Lamping Option (Voltage) Housing Finish Option


Model		Lamping Options		Finish	Options
Model Number	Dimensions				
Surface Mount OW1720	W 14" (356 mm)	※1TF32	1CH150T6	PTD	BCS XPS
	H 14" (356 mm)	1N150	1PH70		
	D 8-5/8" (219 mm)	1CH70T6	1PH100		
	MC 7" (178 mm)				
Recessed Mount OW1722	W 14" (356 mm)	※1TF32	1CH150T6	PTD	BCS XPS
	H 14" (356 mm)	1N150	1PH70		
	D 4-3/4" (121 mm)	1CH70T6	1PH100		
	RD 5-1/4" (133 mm)				
Surface Mount OW1724	W 18" (457 mm)	※1TF32	1CH150T6	PTD	BCS XPS
	H 18" (457 mm)	1N150	1PH70		
	D 8-5/8" (219 mm)	1CH70T6	1PH100		
	MC 9" (229 mm)				
Recessed Mount OW1726	W 18" (457 mm)	※1TF32	1CH150T6	PTD	BCS XPS
	H 18" (457 mm)	1N150	1PH70		
	D 4-3/4" (121 mm)	1CH70T6	1PH100		
	RD 5-1/4" (133 mm)				
Surface Mount OW1728	W 14" (356 mm)	※1TF32	1CH150T6	PTD	BCS XPS
	H 14" (356 mm)	1N150	1PH70		
	D 8-5/8" (219 mm)	1CH70T6	1PH100		
	MC 7" (178 mm)				
Recessed Mount OW1730	W 14" (356 mm)	※1TF32	1CH150T6	PTD	BCS XPS
	H 14" (356 mm)	1N150	1PH70		
	D 4-3/4" (121 mm)	1CH70T6	1PH100		
	RD 5-1/4" (133 mm)				

LINE DRAWINGS


OW1720 / OW1724




OW1722 / OW1726



OW1728



OW1730



Door Height = 7'
 Ceiling Height = 9'
 Silhouette Height = 6'

ABBREVIATION KEY

※ Configuration operates TF26 or TF32 lamp options and can be labeled up to the highest wattage allowed

Dimensions	
W	Width
H	Height
D	Depth (measured from wall to front of fixture)
RD	Recessed Depth
MC	Mounting Center (measured from top of fixture to center of junction box)

Lamping Options (Voltage)

※TF26	26w triple, 4-pin GX24q-3 base, FLR (MVOLT; 347V)
※TF32	32w triple, 4-pin GX24q-3 base, FLR (MVOLT; 347V)
	TF lamping increases RD (recessed depth) dimension to 6-1/2"
N150	150w A-21, medium base, INC (120V)
CH70T6	70w T-6, G12 base, ceramic MH (MTAP; 347V)
CH150T6	150w T-6, G12 base, ceramic MH (MTAP; 347V)
PH70	70w ED-17, medium base, pulse start MH (MTAP; 347V)
PH100	100w ED-17, medium base, pulse start MH (MTAP; 347V)

Specify Voltage, MVOLT or MTAP
 MVOLT is a ballast that operates 120V through 277V
 MTAP is a ballast that operates 120V or 277V

Finishes (see inside back cover)

PTD	Painted - specify color code (ex. BRNZ for Bronze)
-----	--

Options

BCS	Brightness control shield for steep viewing angle
XPS	Express 10 day shipping

PHOTOMETRICS and BIM


Complete BIM (Building Information Modeling) and photometric files for these models may be downloaded from www.visalighting.com

Reports

IES File Number	LER	Report	page
OW1720-1PH100	49	05929	412
OW1722-1PH100	49	05929	412
OW1724-1PH100	49	05929	412
OW1726-1PH100	49	05929	412
OW1728-1PH100	49	05929	412
OW1730-1PH100	49	05929	412

See report on indicated page for complete detail

Candela Distribution



SOUTHRIDGE™



OW1724-TG7042






OW1730-BMAT
Luminous Acrylic

FEATURES

- 5 year product warranty
- Fabricated metal front shield
- Cast aluminum, fully gasketed and sealed lamp chamber with clear tempered glass enclosure
- Oven cured no VOC acrylic powder coat
- Selection of front shield styles
- 1/8" thick white acrylic diffuser, F1 rated, UV stable, UL-94 HB Flame Class rated (OW1728 and OW1730 only)
- Front shield features snap lock for easy tool-less relamping
- HID or incandescent lampping
- Remote mounted HID ballast with long distance ignitor standard, 50' maximum ballast to lamp distance, PH70(347V) is 20' maximum, PH100(347V) is 15' maximum
- Recessed or surface mount housing
- Recessed mount housing for shallower extension from wall
- Surface mounts to standard electrical junction box (by others) with provided hardware
- UL wet location listed for mounting 4' above grade

COMPANIONS



SUGGESTED VARIATIONS

- Increase front shield up to 24" maximum
- Colored front diffuser or glass lamp enclosure
- Custom cutout or logo in front shield
- Alternate lampping up to rated wattage listed

