

4500 Dundas Series

Model	Description	Overall Dimensions						Specific Dimensions													
		Width (in.)	(mm.)	Depth (in.)	(mm.)	Height (in.)	(mm.)	Back Height (in.) (mm.)		Seat Height (in.) (mm.)		Back Width (in.) (mm.)		Seat Depth (in.) (mm.)		Seat Width (in.) (mm.)		Weight (lbs.) (kg.)		Volume Reg/K.D. (cu.ft.) (cu.ft.)	
4500DLX	High Back Management	25	635	27 1/2	698	43-46 1/2	1092-1181	27	686	16-20 1/2	406-521	20	521	19	482	21	533	50	23	17 / 12	0.48 / 0.34
4500D	Mid Back Management	24	609	27	686	34 1/2-38	876-965	20	508	16 1/2-20	406-521	18	457	19	482	20	521	40	18	14 / 10	0.40 / 0.28
4500	Low Back Management	24	609	26	660	32-35 1/2	813-902	17	432	16 1/2-20	406-521	18	457	19	482	20	521	39	18	12 1/2 / 10	0.35 / 0.28
4501	Guest-Armchair	21 1/2	546	25 1/2	648	33 1/2	851	16	406	18	457	18	457	19	482	18	457	31	14	11	0.31
4502	Guest-Cantilever	21 1/2	546	25 1/2	648	33 1/2	851	16	406	18	457	18	457	19	482	20	521	35	16	11	0.31
4503	Guest-Sled Base With Arm	21 1/2	546	24	609	33 1/2	851	16	406	18	457	18	457	19	482	18	457	32	15	11	0.31
4509	Guest-Armless	21 1/2	546	25	635	33	838	16 1/2	419	18	457	18	457	19	482	18 1/2	470	28	13	11	0.31



Standard Features •

- Swivel-tilt mechanism (4500DLX, 4500D, 4500) (Type 8) Pneumatic height adjustment, tension control.
- Contoured back for added lateral back support.
- Built-in lumbar support.
- High density seat and back foam for comfort and durability.
- Waterfall seat to reduce muscle fatigue.
- Oval steel frame and/or arms finished with high impact, textured, black *Crinkle* epoxy powder coat electrostatically applied for corrosion resistance.
- Fully upholstered seat and back.
- 5 prong heavy duty nylon base.
- 2" dual wheel carpet casters.
- Finish - mechanism, arms, base, casters and trim available in black only.
- Guest chair (4501, 4503, 4509) designed with angled back leg for added stability.
- Cantilevered sled chair (4502) frame reinforced for added strength.
- ANSI/BIFMA.

Options - ○

Model	Description	Miscellaneous			
		Type 18 Swivel Tilt-Lock - TL	Upholstered Arm Caps - UC	Soft Tilt Casters - TC	Fire Code #133 - FR
	To specify any option(s) simply add the suffix(s) to the model number. (ie) 4500D-TL				
4500DLX	High Back Management	○	○	○	○
4500D	Mid Back Management	○	○	○	○
4500	Low Back Management	○	○	○	○
4501	Guest-Armchair		○	○	○
4502	Guest-Cantilever		○	○	○
4503	Guest-Sled Base With Arm		○	○	○
4509	Guest-Armless				○

Mechanism User Guide



- (A) Tension Knob**
Turn clockwise to increase tension, turn counter-clockwise to decrease tension
- (L) Single Position Tilt Lock**
Push lever in to lock chair in forward position, pull lever out to unlock.
- (Q) Pneumatic Height Adjustment**
To lower, lift paddle while seated. To raise, lift paddle with your weight off seat.

General Information:

- Soft wheel casters should be specified for hard floor surfaces.
- Upholstery
All models 2 yds / chair except 4500DLX 2 1/2 yd.
- Patented
- Fabric Selection
To specify simply add the suffix provided on the fabric card swatch of your choice to the chair model number (ie) 4500 -E01 (Epic Espresso)

Nightingale Inc.

2301 Dixie Road, Mississauga, Ontario, Canada L4Y 1Z9
Tel: (905) 896-3434 Toll Free: 1-800-363-8954
Fax: (905) 896-7011 Toll Free: 1-800-637-6784
E-mail: info@nightingalechairs.com
Website: www.nightingalechairs.com

Showrooms in

• Toronto • Vancouver • Montreal

Printed in Canada