

4200 Chorus Series

Model	Description	Overall Dimensions						Specific Dimensions													
		Width (in.) (mm.)		Depth (in.) (mm.)		Height (in.) (mm.)		Back Height (in.) (mm.)		Seat Height (in.) (mm.)		Back Width (in.) (mm.)		Seat Depth (in.) (mm.)		Seat Width (in.) (mm.)		Weight (lbs.) (kg.)		Volume Reg/K.D. (cu.ft.) (cu.mt.)	
4200D	High Back Executive	24	609	28 1/2	724	40-43 1/2	1016-1105	23	584	18-21 1/2	457-546	20	508	19	482	20	508	45	20	17 / 12	0.48 / 0.34
4200	Mid Back Management	24	609	27	686	36-39 1/2	914-1003	19	482	18-21 1/2	457-546	20	508	19	482	20	508	42	19	14 / 12	0.40 / 0.34
4201	Guest-Armchair	24	609	27	686	34	863	19	482	18	457	20	508	19	482	20	508	34	15	14	0.40
4202	Sled Base With Arm	24	609	27	686	35	889	19	482	18	457	20	508	19	482	20	508	42	19	14	0.40



Standard Features •

- Swivel-tilt mechanism (4200D, 4200) (Type 8) Pneumatic height adjustment, tension control.
- Compound curve seat and back shell with gentle lumbar curve for correct posture.
- Waterfall seat design to reduce muscle fatigue.
- High density seat and back foam for comfort and durability.
- Injection molded plastic armrests.
- Fully upholstered seat and back.
- 5 prong heavy duty nylon base.
- 2" dual wheel carpet casters.
- Finish - mechanism, arms, base, casters and trim available in black only.
- California fire code #117.
- Guest chair (4201) designed with angled back leg for added stability.
- Cantilivered sled chair (4202) frame reinforced for added strength.
- Oval steel frame (4201, 4202) finished with high impact, textured, black **Crinkle** epoxy powder coat electrostatically applied for corrosion resistance.
- ANSI/BIFMA.

Options - ○

Model	Description	Misc.	
	To specify any option(s) simply add the suffix(s) to the model number. (ie) 4200D-TL	Type 18 Swivel Tilt Lock - TL	Soft Tilt Casters - TC
4200D	High Back Executive	○	○
4200	Mid Back Management	○	○
4201	Guest-Armchair		
4202	Sled Base With Arm		

Mechanism User Guide



- Ⓐ **Tension Knob**
Turn clockwise to increase tension, turn counter-clockwise to decrease tension
- Ⓕ **Single Position Tilt Lock**
Push lever in to lock chair in forward position, pull lever out to unlock.
- Ⓖ **Pneumatic Height Adjustment**
To lower, lift paddle while seated. To raise, lift paddle with your weight off seat.

General Information:

- Soft wheel casters should be specified for hard floor surfaces.
- Upholstery
All models 2 3/4 yds / chair.
- Patent pending
- Fabric Selection
To specify simply add the suffix provided on the fabric card swatch of your choice to the chair model number.
(ie) 4200 -E01 (Epic Espresso)

Nightingale Inc.

2301 Dixie Road, Mississauga, Ontario, Canada L4Y 1Z9
 Tel: (905) 896-3434 Toll Free: 1-800-363-8954
 Fax: (905) 896-7011 Toll Free: 1-800-637-6784
 E-mail: info@nightingalechairs.com
 Website: www.nightingalechairs.com

Showrooms in

- Toronto
- Vancouver
- Montreal