

# Talo 90-120-150-180-240 suspension

## Talo 90-120 suspension catamaran



Neil Poulton

Cable suspension mounted luminaires for direct and indirect fluorescent lighting.

- body with profiles in extruded aluminum and end caps in die-cast aluminum
- available lengths: 36", 48", 60", 71", and 95"
- available in white or silver grey powder coated finish
- upper diffuser in clear molded polycarbonate, lower diffuser in opaline molded polycarbonate
- suspension supporting/feeding cables with clear teflon coating
- ceiling canopy in steel with cover in molded thermoplastic with white or silver grey powder coated finish
- mounting to standard electrical junction boxes
- equipped with thermally protected, class P, high power factor 120V electronic fluorescent ballast (277V optional)

LISTING  
Intertek ETL  
Report No. 3020854LST

PHOTOMETRICS  
Candela Polar Diagram, Candela Tabulation  
and Coefficients of Utilization available as an  
I.E.S. file for download at [www.artemide.us](http://www.artemide.us)



Talo 90 suspension  
fluorescent source  
• 1x39W (G5/T5 HO).....

Talo 90 suspension catamaran  
fluorescent source  
• 2x39W (G5/T5 HO).....

Talo 120 suspension  
fluorescent source  
• 1x54W (G5/T5 HO).....

Talo 120 suspension catamaran  
fluorescent source  
• 2x54W (G5/T5 HO).....

Talo 150 suspension  
fluorescent source  
• 1x80W (G5/T5 HO).....

Talo 180 suspension  
fluorescent source  
• 2x39W (G5/T5 HO).....

Talo 240 suspension  
fluorescent source  
• 2x54W (G5/T5 HO).....

