

# Acorn Ceiling

RENAISSANCE

16"

24"


32"

## Specifications:


- Trim rings are spun from .063" thick base material (brass or aluminum) or 18 gauge steel (plated or painted).
- Chassis is formed from 18 gauge cold-rolled steel.
- Formed acrylic bowl with a minimum wall thickness of .118". Opal finish is standard.
- Integral fluorescent ballasts are HPF electronic with low harmonic distortion.
- Ballasts are thermally protected and have Class "A" sound rating.
- Backplate attaches to standard 4" octagonal junction box.
- UL listed (US and Canada) for damp locations. (Not recommended for exterior use.)

Design modification rights reserved.


## Traditional Trim



**RIC1030**



**RIC1032**



**RIC1034**



**RIC1030**

Antique Solid Brass

Sample model number: **RIC1032 - 1N150 - 120 - BAL - HP02**

| Select Style          | Select any Lamping<br>(bowl illumination) | Lamping Detail<br>(bowl illumination) | Optical<br>Pkg. Photometry | Select Voltage                                    | Select Finish                                                                       | Select Options                                                                            |
|-----------------------|-------------------------------------------|---------------------------------------|----------------------------|---------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|
| 16"<br><b>RIC1030</b> | <b>2F13</b>                               | (2) CFQ13W/G24q                       | A NA                       | <b>120</b><br><b>277</b>                          | <b>PT</b> Painted. (Include Paint Number.)                                          | <b>SP</b> Spacer canopy (Not available for RIC1034.)                                      |
|                       | <b>2F26</b>                               | (2) CFQ26W/G24q                       | A NA                       |                                                   | <b>PBR</b> Polished solid brass                                                     | <b>F</b> Fuse option                                                                      |
|                       | <b>1N60</b>                               | 60W A19 INC                           | B E433-35                  |                                                   | <b>BBR</b> Brushed solid brass                                                      | <b>EMI<sup>1</sup></b> Emergency ballast(s) integral (RIC1032 requires SP-Spacer canopy.) |
|                       | <b>1F22</b>                               | 22W CIRC T5                           | C NA                       |                                                   | <b>ABR</b> Antique solid brass                                                      | <b>EMR</b> Emergency ballast(s) remote                                                    |
| 24"<br><b>RIC1032</b> | <b>3N60</b>                               | (3) 60W A19 INC                       | D NA                       | <b>CPBR</b> Chrome plated polished brass          | <b>SBA</b> Sandblasted acrylic                                                      |                                                                                           |
|                       | <b>1N150</b>                              | 150W A21 INC                          | E NA                       | <b>BAL</b> Brushed aluminum                       | <b>HP01</b> Silver hand-painted acrylic                                             |                                                                                           |
|                       | <b>3F13</b>                               | (3) CFQ13W/G24q                       | F E433-34                  | <b>ABST</b> Antique brass over steel              | <b>HP02</b> Beige hand-painted acrylic                                              |                                                                                           |
|                       | <b>2F26<sup>1</sup></b>                   | (2) CFQ26W/G24q                       | G NA                       | <b>BBST</b> Brushed brass over steel              | <b>HP03</b> Amber hand-painted acrylic                                              |                                                                                           |
|                       | <b>2F39<sup>1</sup></b>                   | (2) FT39W/2G11                        | G NA                       | <b>CPST</b> Polished chrome over steel            | <b>FIN</b> Finial option                                                            |                                                                                           |
|                       | <b>1F40</b>                               | 40W CIRC T5                           | C NA                       | <b>PBST</b> Polished brass over steel             |  |                                                                                           |
| 32"<br><b>RIC1034</b> | <b>3F39</b>                               | (3) FT39W/2G11                        | H NA                       | <i>See Finish Selection Guide, pages 268-269.</i> |                                                                                     |                                                                                           |
|                       | <b>3F39DM</b>                             | (3) FT39W/2G11                        | H NA                       |                                                   |                                                                                     |                                                                                           |
|                       | <b>4F39</b>                               | (4) FT39W/2G11                        | I NA                       |                                                   |                                                                                     |                                                                                           |
|                       | <b>3N100</b>                              | (3) 100W A19 INC                      | D NA                       |                                                   |                                                                                     |                                                                                           |

DM = Dimming ballast(s) provided

If Photometry is not available,  
consult factory for further details.

<sup>1</sup>Denotes lamping options available with **EMI**  
(RIC1032 requires **SP**-Spacer canopy)

For further detail on options,  
see Technical Notes on page 264.

## OPTICAL PACKAGES

