Drum Arm Sconce & Sconce







Stepped Trim



RIW1060 Brushed Brass



RIW1050 Chrome Plated Polished Brass

16"


24"


Specifications:

- Trim rings are spun from .063" thick base material (brass or aluminum) or 18 gauge steel (plated or painted).
- Chassis is formed from 18 gauge cold-rolled steel.
- Formed acrylic bowl with a minimum wall thickness of .118".
 Opal finish is standard.
- Integral fluorescent ballasts are HPF electronic with low harmonic distortion.
- H.I.D. ballasts are magnetic HX-HPF for 150 watt and below.
 Magnetic CWA-HPF ballasts are used for over 150 watts. H.I.D. ballasts are remote mounted.
- Ballasts are thermally protected.
- Fluorescent ballasts have a Class "A" and H.I.D. a Class "B" sound rating.
- Backplate attaches to standard 4" octagonal junction box.
- UL listed (US and Canada) for damp locations. (Not recommended for exterior use.)

Design modification rights reserved.


Sloped Trim






MC = Mounting Center

Stepped Trim



RIW1060



Sample model number: RIW1050 - 1T75/1N25 - 120 - BAL - HP02



	Select Style	Select any Lamping (indirect/bowl illumination				Select Voltage		Select Finish		Select Options
		_	Lamping Detail (indirect - bowl illumination)	Optica Pkg.	I Photometry			~		~
16"	RIW1050 RIW1060	2F13	(2) CFQ13W/G24q	А	NA	120 277	PT	Painted. (Include Paint	F	Fuse option (M and F)
		1T75/1N25	75W DC BAY QTZ - 25W T10 INC	В	NA			Number.)	RPI	Remote ballast support tray
		1N75	75W A19 INC	С	NA		PBR	Polished solid brass	EMR	Emergency ballast(s) remote
							BBR	Brushed solid brass	SBA	Sandblasted acrylic
24"	RIW1052 RIW1062	2F39/1F13	(2) FT39W/2G11 - CFQ13W/G24q	D	E433-86		ABR	Antique solid brass	SS	Separate switching
		1F26/1F13	CFQ26W/G24q - CFQ13W/G24q	E	E433-86		CPBR	Chrome plated polished brass	HP01 HP02	Silver hand-painted acrylic
		1F26DM/1F13	CFQ26W/G24q - CFQ13W/G24q	E	E433-82		BAL	Brushed aluminum		Beige hand-painted acrylic
		1N150	150W A21 INC	F	NA		ABST	Antique brass over steel	HP03	Amber hand-painted acrylic
		1T150/1N25	150W T10 QTZ - 25W T10 INC	E	E433-82R		BBST	Brushed brass over steel		er detail on options, nical Notes on page 264.
		1M150/1F13	150W T6/G12 MH - CFQ13W/G24q	E	NA		CPST	Polished chrome over steel	366 166	minuai Notes on paye 204.
	DM = Dimming ballast(s) provided			If Photometry is not available, consult factory for further details.			PBST	Polished brass over steel		
							See Finish Selection Guide, pages 268-269.			

OPTICAL PACKAGES

