



Interior Ceiling Mount



Yoke





Specifications:

- **Extruded** - Extruded .125" aluminum housing.
- **Solid** - Roll-formed .05" aluminum housing.
- **Perforated** - Roll-formed, perforated 18 gauge steel housing.
- Cast aluminum end caps with flush-mounted fasteners.
- Housing is field adjustable for application specific aiming and can be mechanically locked in the desired position.
- H.I.D and Tungsten Halogen luminaries utilize a segmented, 95% reflective, specular clear, aluminum reflector. Impact and heat-resistant, tempered glass lens.
- Yoke bracket is die-formed from 14 gauge steel.
- Hub mounting utilizes a cast aluminum hub.
- Formed aluminum cover to fit over a standard 4" junction box.
- The Ceiling Mount Kit utilizes a yoke bracket with a cover plate that mounts directly to a standard 4" junction box. Allows for 356° horizontal adjustability.
- Housing, endcaps, brackets, and cover plates painted to match. Standard finish is thermoset polyester powder coat. All metal surfaces go through a 5-stage pretreatment process prior to powder coat application.
- H.I.D. ballasts are remote, encased and potted, magnetic CWA-HPF design (120/277 volt operation). Ballasts are thermally protected and have a Class "B" sound rating.
- UL listed (U.S. and Canada) for damp locations. (Not for exterior use.)

Hub



Ceiling Mount Kit



Assistance Available: Please see our website, or call 262-242-1420 for more specific product information, applications assistance or modification requests.

ECHO 6.0

Remote Ballast

FT	PW	VG	Lamp Wattage Range	Lamp
				FL
			39-150W	MH
			150-250W	TH

SELECT STYLE

Mounting	Housing
EIC 2000	Yoke Extruded
EIC 2002	Yoke Perforated
EIC 2004	Yoke Solid
EIC 2006	Hub Extruded
EIC 2008	Hub Perforated
EIC 2010	Hub Solid
EIC 2012	CM Kit Extruded
EIC 2014	CM Kit Perforated
EIC 2016	CM Kit Solid

SELECT LAMPING

Lamping Detail
1M39 (1) 39W T6 CMH/G12
1M70 (1) 70W T6 CMH/G12
1M150 (1) 150W T6 CMH/G12
1T150² (1) 150W T4 DC BAY QTZ
1T250² (1) 250W T4 DC BAY QTZ

² 120 volt only.

For additional lamping details and options, see Technical Notes on pages 160-161.

SELECT OPTICAL PACKAGE

FT Forward Throw
PW Plane Wash

SELECT VOLTAGE

120
277

See SPI Finish Selection Guide on pages 168-169.

Other voltages/frequencies are available. For additional details and options, see Technical Notes on page 166 or consult factory for information.

SELECT FINISH

PT_ Painted. (Include Paint Number)
--

SELECT OPTIONS

CS Cut-off Shield.
RPI Remote ballast support tray. (metal halide lamping)
F Fuse. (metal halide lamping)
Q* Standby Quartz Lighting. (for 39W and 70W metal halide lamping, 75W quartz auxiliary lamping)

For further details on Options, see Technical Notes on page 165.

*Only available with Forward Throw (FT) Optics.

Reflections
Wall
Ceiling
Pendant

3.5
Wall
Ceiling
Pendant

5.0
Wall
Ceiling
Pendant
Pier
Cove
MRI
Shapes

6.0
Wall
Ceiling
Pendant
Pier
Cove
MRI

9.0
Wall
Ceiling
Pendant
Pier
Cove
MRI
Shapes

16.5
Wall
Pier
Pendant

Exterior

Lightruss