



## Apollo Table Specifications:

### Top Construction:

Special•T table tops are nominal 1-1/4" thick. Core is 1-1/8" thick 45# M3 industrial strength density particle board. The top surface is laminated with High Pressure Laminate (HPL) and the bottom is covered with a balance backer. Tables 66" and longer include steel support to prevent sagging. Standard edges are T-mold and 3mm PVC. Other edges available\*:

- Fancy Vinyl
- Fancy Vinyl with Flat Sides
- Wood
- PurTech Urethane
- PurTech Urethane with Flat Sides
- PurWood Urethane
- PurWood Urethane with Flat Sides

\*Custom edges may not be available with all shapes and sizes.  
See [www.SpecialT.net](http://www.SpecialT.net) → product page → edge tab for edge offerings.

### Base Construction:

Bolted  
Base height: 27.75"  
Columns: 2" diameter, 14 gauge steel  
Feet: 2" diameter, 14 gauge steel, steel endcaps  
Mounting plates: 6" x 12" x 7/32" steel  
Levelers: 1-3/8" diameter, 1" long  
Finish: powder coat  
Load capacity: 330 lbs. (200kg) vertical load rating per base

### Options:

- Casters
- T or C leg
- Folding
- Bar height
- Perforated panels
- Modesty panels
- Grommets
- Wire management
- Table joiners

For easy installation, tops are pre-drilled.  
The base positioning is as following:

36" - 48"	3.5" from the edge to column center
54"	4" from the edge to column center
60" - 72"	6" from the edge to column center
84"	12" from the edge to column center
96"	12" from the edge to column center



*Perforated Panel Option*



*C-Leg Option*