# MF1055 PARK TABLE



Size: 72" x 64" x 31" Weight: 225 lbs

Construction: Panels - 11 Gauge Perforated Steel - Metal-Armor Coated

Framework - 2" Diameter - 12 Gauge Galvanized Tube - Metal-Armor Coating - With U. V. Inhibators on Panels -

Vandal Resistant Security Head Bolts - Baked-On Polyester

Powder Coat on Framework

Other Options: Permanent Anchoring Kit Available From Site Furnishings

Panel Color Options: Black - Green - Yellow - Beige - Brown - Red - Blue - Burgundy - Federal Green - Gray

Frame Color Options: Black - Sand - Gray - Red - Blue

\*\* Custom colors are available upon request

#### **Metal Form Specifications**

Finish Specification

Metal Armor Coating Performance Properties

Thermoplastic functional polyethylene copolymer-based coating

Standard Features:

Coverage: 20mils minimum

Flexibility: 1/8", no cracks ASTM D 533

Adhesion: >1000 psi/(5A) ASTM D 4541/ASTM D 3359

Scored and unscored/no peeling or removal

Impact Resistance: >384 in/lbs ASTM D 2794 Gloss: At 60 degrees – 35-60 ASTM D 523

Delta Shift: 1.77 1400 MJUV = 5 yrs (color tested: Red)

Hardness: Shore D-48 ASTM 2240
Taber Abrasion: 90 mg loss - CS10 wheel ASTM D 4060

100 mg loss – CS17 wheel

Salt Spray Resistance: >4000 hrs ASTM B 117 Humidity Resistance: No blistering or loss of ASTM D 2247

Gloss after 1000 hrs

Smoke Development: 10 Flame spread index ASTM E 84

10 Smoke developed index

Chip Resistance: 8A ASTM D 3170

Environmental

VOC Content: 0, 100% solids

Special Approvals

FDA approved for direct food contact and has USDA compliance for use within the product zone applications.

Health

NFPA Classification:

Flammability: 1


Health: 0 Reactivity: 0


### NOTE:


Leave all connections loose until completely assembled. Secure all fasteners in final assembly.



## SPECIFICATIONS MF 1055 Park Table







ITEM NO.	DESCRIPTION	QTY
1	Table Top	1
2	Seat	2
3	Tubular Legs	2
4	Table Brace	2
5	3/8" x 1" Hex Bolts	16
7	3/8" Flat Washers	16
8	3/8" Nylon Lock Nuts	16

#### 1.1 SUMMARY

A. Section includes: Furnish Metal-Form benches on drawings or specified herein.

#### 1.2 REFERENCES

A. American Society for Testing & Materials

1. ASTM-D533 ASTM-D4541 ASTM-D3359 ASTM-2794 ASTM-D523 ASTM-4060 ASTM-B117 ASTM-D2247 ASTM-E84 ASTM-D3170 ASTM-A569 ASTM-B6 ASTM G26 ASTM-A569/A569M

#### 1.3 SUBMITTALS

A. Submit product data, shop drawings and samples.

- Product Data: Manufacturer's specifications and technical data edited specifically for proposed product, including the following specific information:
  - a. Detailed specification of construction fabrication.
  - b. Manufacturer's installation instructions
  - c. Product warranty
- B. Shop Drawings: Indicate pertinent dimensions, general construction, component connections, anchoring methods, hardware and installation procedures.
- C. Samples as requested by Architect.

#### 1.4 QUALITY ASSURANCE

- A. Qualifications of Manufacturer: Manufacturer to be prequalified by specifier prior to bidding. Failure to comply will result in disqualification of bid. Manufacturer to have at least three years experience in the manufacture of thermo plastic coated steel site furnishings field proven for at least three years.
- B. Warranty: 5 Years Metal Armor Coated Products 2 Years - Framework

#### 1.5 MANUFACTURERS

A. Acceptable manufacturer for thermo plastic coated steel site furnishings to be known as:

Wausau Tile, Inc.

PO Box 1520

Wausau, WI 54402-1520

(800) 388-8728 FAX (715) 355-4627

B. Clarification Note: Drawings and installation specifications are based on manufacturers proprietary literature from Wausau Tile, Inc. Other manufacturers shall comply with minimum levels of material and detailing indicated on drawings or specified herein.