
TF 3175 PT1-2 Table



Options:

Note: Options may change without notice. Call to confirm current options.

Ground & Polished (top)
Misty Gray - Sand - Brown Brick Red - Gray

Smooth Stained Concrete (Pedestal & Legs)
Brick Red - Sand - Gray - Brown

Custom Options Available

Size: 80" L x 36" W x 29-1/2" H installed.

Weight: 1285 lbs. Seating Capacity: 2 persons.

Material: Reinforced concrete.
Reinforcing: 1/4" & 3/8" Dia. steel rebar.

Hardware: None.

Chairs: (2) - 34" L x 22" W x 27-1/2" H. Table: (1) - 34" Sq. x 29-1/2" H.

Anchoring: None.

Features: Game board of ground and polished terrazzo.
Assembly: Use Latapoxy to bond bases together.

Maintenance: Periodically rinse with water and mild detergent.

Re-seal annually or as needed.

Packaging: Banded to pallet.



GENERAL TABLES SPECIFICATIONS

MORTAR JOINT IF ADJOINING MATERIAL IS CONCRETE OR PAVERS 27 1/2" MORTAR JOINT 3/8" TO 1/2" FINISH GRADE CONCRETE SLAB BY OTHERS FLEVATION SECTION TABLE COMPACTED SUB. BASE 9 ∠ 3/8" TO 1/2" MORTAR JOINT-TYP. TEXTURED CORNER BLOCK NINE PART UNIT ASSEMBLY BY 34" MORTAR JOINT IF ADJOINING MATERIAL IS CONCRETE OR PAVERS 0 22 THREE PART UNIT ASSEMBLY BY OTHERS

3/8" TO 1/2" MORTAR JOINT - TYPICAL

WHITE SQ. ON RIGHT

TF3175 & TF3180 GAME TABLE WITH CHAIRS

TF 3175 PT1-2 Table

1.1 SUMMARY

A. Section includes: Furnish Precast Concrete Table indicated on drawings or specified herein.

1.2 REFERENCES

- A. American Society for Testing & Materials
 - 1. ASTM C33 2. ASTM C150 3. ASTM C31

1.5 SUBMITTALS

- A. Submit product data, shop drawings and Samples.
 - Product Data: Manufacturer's specifications and technical data edited specifically for proposed system, including the following specific information:
 - a. Detailed specification of construction fabrication.
 - b. Manufacturer's installation instructions
 - c. Maintenance literature
 - d. Product warranty
 - 2. Shop Drawings: Indicate pertinent dimensions, general construction, component connections anchoring methods, hardware and installation procedures.
 - 3. Samples as requested by Architect.

1.6 QUALITY ASSURANCE

A. Qualifications of Manufacturer: Manufacturer to be prequalified by specifier prior to bidding. Failure to comply will result in disqualification of bid. Manufacturer to have at least five years experience in the manufacturer of precast concrete tables field proven for at least five years.

1.10 WARRANTY

Manufacturer shall submit a written warranty for precast products for the period of two years upon acceptance of products.

2.1 MANUFACTURERS

- A. Acceptable manufacturer for Precast Concrete Tables to be known as Wausau Tile, Inc. Terra-Form Division.
 PO Box 1520, Wausau, WI 54402-1520.
 (800) 388-8728 FAX (715) 355-4627
- B. Clarification Note: Drawings and installation specification are based on manufacturers proprietary literature from Wausau Tile, Inc. Other manufacturers shall comply with minimum levels of material and detailing indicated on drawings or specified herein.
- C. All Precast products for this project shall be of one manufacturer.

2.2 MATERIALS

- A. Portland Cement: ASTM C150 specifications for Portland Cement.
- B. Aggregates: All aggregates to meet ASTM C33 specifications, to be cleaned of foreign matter and properly graded to size.
- C. Coloring: Pigments used shall be inorganic, resistant to alkalinity and used as per manufacturers recommendations.

#



∠ 3/8" TO 1/2" MORTAR JOINT-TYP