
TF 1223 Model E Recycle Waste Container w/Ribs & Recycle Top & Liner



Options

(Note: Options may change without notice. Call to confirm current options.)

Weatherstone:

Sand - Gray - Brown - Buff - Cream - Soulard Green Light Charcoal - French Gray - Brick Red

Exposed Aggregate:

Tan w/Gray Matrix - Tan w/Brown Matrix Tan w/Sand Matrix - Misty Gray w/Gray Wyoming White

<u>Granitex (GTX)</u> 2078F, 4028F, 6208F, 1168F, 2098F

Glass

Clear - Emerald - Blue - Amber Champaign - Charcoal

Custom Options Available

TF 1619 Liner

Size: 18" x 11" x 31" H. Weight: 7 lbs. each.

Capacity: (3) 14 gallons each. Totaling 42 gallons.

Material: Recyclable plastic.

Packaging: May vary.

Size: 29" Dia. x 39" H.

Weight: 950 lbs.

Capacity: (3) - 14 gallon individual liners totaling 42 gallons.

Material: Reinforced Concrete.

Colors/Surfaces: See options9.

Wall Thickness: 2" at top with 2% pitch.

Hardware: (4) - 1/2" Dia. elevator bolts, inserted on site.

(4) - 1/2" Dia. zinc alloy inserts.
(1) - 1/4" Dia. zinc alloy insert.
(2) - 5/8" Dia. lifting inserts.

Packaging: Palletized.

Maintenance: Occasionally rinse with water & mild detergent.

Re-seal annually.

Anchoring: Optional.

Logo Options: Cast-in-place logo.

Note: International recycling logo standard.

TF 1516 Recycle Top

Size: 25" Dia. x 5" H.

Weight: 3 lbs.

Material: Polyethelyne Plastic.

Colors: Blue

(Color may change without notice.)

Hardware: (1) - Security Cable.

(1) - Shouldered allen bolt.

(1) - 1024 Washer

(1) - 1024 Hex head bolt (1) - Shouldered screw

Opening: Square: 4-1/2" Sq.


Circle: 8" Dia.


Oval: 7-3/4" x 4 1/2".


Packaging: Shipped in carton.

Maintenance: Clean with mild soap and water.
Features: (3) individual recycling compartments.

Installation: Attach to container with security cable.







1.1 SUMMARY

A. Section includes: Furnish Precast Concrete Waste Containers indicated on drawings or specified herein.

1.2 REFERENCES

- A. American Society for Testing & Materials
 - ASTM C33
 ASTM C150
 ASTM C31

1.5 SUBMITTALS

- A. Submit product data, shop drawings and samples.
 - 1. Product Data: Manufacturer's specifications and technical data edited specifically for proposed system, including the following specific information:
 - a. Detailed specification of construction fabrication.
 - b. Manufacturer's installation instructions
 - c. Maintenance literature
 - d. Product warranty
 - Shop Drawings: Indicate pertinent dimensions, general construction, component connections anchoring methods, hardware and installation procedures.
 - 3. Samples as requested by Architect.

1.6 QUALITY ASSURANCE

A. Qualifications of Manufacturer: Manufacturer to be prequalified by specifier prior to bidding. Failure to comply will result in disqualification of bid. Manufacturer to have at least five years experience in the manufacturer of precast concrete waste containers field proven for at least five years.

1.10 WARRANTY

Manufacturer shall submit a written warranty for precast products for the period of two (2) years upon acceptance of products.

2.1 MANUFACTURERS

- A. Acceptable manufacturer for Precast Concrete Waste Containers to be known as:
 - Wausau Tile, Inc. Terra-Form Division. PO Box 1520, Wausau, WI 54402-1520. (800) 388-8728 FAX (715) 355-4627
- B. Clarification Note: Drawings and installation specification are based on manufacturers proprietary literature from Wausau Tile, Inc. Other manufacturers shall comply with minimum levels of material and detailing indicated on drawings or specified herein.
- C. All Precast products for this project shall be of one manufacturer.

2.2 MATERIALS

- A. Portland Cement: ASTM C150 specifications for Portland Cement.
- B. Aggregates: All aggregates to meet ASTM C33 specifications, to be cleaned of foreign matter and properly graded to size.
- C. Coloring: Pigments used shall be inorganic, resistant to alkalinity and used as per manufacturers recommendations.

#