

Cronos

PORCELAIN STONE


- Features the beauty and elegance of terrazzo
- Available in polished and unpolished finishes
- All tiles are rectified, allowing extremely tight grout joints
- Large sizes create dramatic visual appearance



VS110 Azul



VS111 Beige




VS112 Blanco



VS113 Carmel




VS114 Gris



VS115 Negro



VS116 Nuez



VS117 Tejas

Sizes Available

Surface/Texture	Size Actual	Size	Thickness
PO/UP	18 x 18	17-1/2 x 17-1/2	3/8

Product Performance

Abrasion Wear	>200	ASTM C501
Bond Strength	>200 psi	ASTM C482
Break Strength	425 lbs.	ASTM C648
Coefficient of Friction		
Unpolished (Dry)	>0.6	ASTM C1028-89
Unpolished (Wet)	>0.8	ASTM C1028-89
Polished (Dry)	N/A	ASTM C1028-89
Polished (Wet)	>0.6	ASTM C1028-89
Water Absorption	<0.10%	ASTM C373

Recommended Usage

Crossville porcelain stone products are recommended for interior walls and floors and exterior walls in both residential and commercial applications.

Care and Maintenance

Regular cleaning is the best way to keep your porcelain stone looking new for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville Porcelain Stone products is available at www.crossvilleinc.com.

Shade & Texture Index

Cronos has a shade variation of V2.



V1



V2



V3



V4

V1=Uniform Appearance
V2=Slight Variation
V3=Moderate Variation
V4=Substantial Variation



Crossville, Inc. • P.O. Box 1168, Crossville, TN 38557
Phone: 931.484.2110 • Fax: 931.456.2956
E-Mail: crossc@crossvilleinc.com
www.crossvilleinc.com