



## EXTERNAL THREAD STA-LOK SWAGELESS

| Part # RH | Part # LH | ø Rope in<br>mm | a   | b   | c   |
|-----------|-----------|-----------------|-----|-----|-----|
| 851-0300  | 852-030 0 | 3               | M6  | 62  | 52  |
| 851-0400  | 852-0400  | 4               | M8  | 64  | 54  |
| 851-0500  | 852-050 0 | 5               | M10 | 78  | 67  |
| 851-0600  | 852-060 0 | 6               | M12 | 93  | 83  |
| 851-0800  | 852-080 0 | 8               | M16 | 110 | 95  |
| 851-1000  | 851-100 0 | 10              | M20 | 129 | 115 |
| 851-1200  | 852-120 0 | 12              | M22 | 168 | 138 |
| 851-1400  | 852-140 0 | 14              | M24 | 172 | 139 |
| 851-1600  | 852-160 0 | 16              | M27 | 205 | 171 |
| 851-1900  | 852-190 0 | 19              | M30 | 281 | 228 |
| 851-2200  | 852-220 0 | 22              | M30 | 281 | 228 |
| 851-2600  | 852-260 0 | 26              | M36 | 297 | 232 |

Material 1.4401/AISI 316 – Ideal for Self-Assembly, Breaking Strength:  
90 % of rope Max. Breaking Load



e-mail: [sales@decorcable.com](mailto:sales@decorcable.com)  
Toll Free: (800)444-6271