

CONSTRUCTION:	Pattern Textured Loop
FACE FIBER:	Nylon with Post-Production and High Rrecycled Content Pre-consumer Content
DYE METHOD:	Yarn / Solution
GAUGE:	1/12
STITCHES PER INCH:	9.83 (Minimum)
PILE HEIGHT:	5/32 (Minimum)
TUFTED YARN WEIGHT:	21 ounces per square yard (Minimum)
PRIMARY BACKING:	100% Synthetic
SECONDARY BACKING:	Infinity® RE with a minimum 10% post-consumer and 20% pre-consumer recycled content by total product weight.
WEAR WARRANTY:	Lifetime Limited Wear Warranty
BACKING WARRANTY:	Lifetime Limited Backing Warranty

METHENAMINE PILL TEST (ASTM-D-2859):	PASSES
FLOORING RADIANT PANEL TEST (ASTM-E-648):	CLASS I (DIRECT GLUE)
N.B.S. SMOKE CHAMBER TEST (ASTM-E-662):	<450 (FLAMING MODE)
DIMENSIONAL STABILTY AACHEN TEST:	PASSES
ELECTROSTATIC PROPENSITY TEST (AATCC 134):	< 3.0 KV
AVERAGE DENSITY:	4846 (Minimum)
STANDARD SIZE:	24" x 24" *(Quarter Turn or Shuffled) *Other installation methods at owner's discretion

CRI IAQ GREEN LABEL PLUS ID: GLP7616

(Minimum) - Due to the nature of this unique product, minimum specifications are listed. These variances will not affect the performance of the product.

Due to yarn variances, each run will slightly differ in color.

RELEASEABLE ADHESIVE:	MANNINGTON'S INFINITY ADHESIVE
CRI IAQ ADHESIVE TESTING CERTIFICATION:	GLP-70522
BOND WARRANTY:	Lifetime Limited Warranty When Used With Artworks / Modular Carpet Tile

**specifications are subject to nominal manufacturing variances

**specifications are subject to change without notice when shortages occur or when technological advances provide improved product performance



adds
LEED
VALUE