

Quartzite

PORCELAIN STONE

- Combines the beauty of natural quartzite with the quality characteristics of Porcelain Stone® by Crossville
- Unique color application effect provides a wide variety of visual appearances on the tile surface

- Subtle veining runs through texture
- Available in multiple sizes and four great colors
- Easy to install and maintain



AV121 Cream Multicolor



AV122 Green Multicolor



AV123 Noce Multicolor



AV124 Black Multicolor



3" x 3" Mosaics Tile



4" Corner / 4" Border



6" Corner / 6" Border

Sizes Available

Surface/Texture	Size	Actual Size	Thickness
UPS	3 x 3"	2-3/4 x 2-3/4	3/8
UPS	3 x 6"	2-3/4 x 5-5/8	3/8
UPS	6 x 6"	5-3/4 x 5-3/4	3/8
UPS	12 x 12"	11-3/4 x 11-3/4	3/8
UPS	12 x 18"	11-3/4 x 17-3/4	3/8
UPS	18 x 18"	17-3/4 x 17-3/4	3/8

Coordinating Trim available in all colors:

3" x 6" Bullnose (6" side)	2-3/4 x 5-5/8	3/8
6" x 3" Bullnose (3" side)	5-5/8 x 2-3/4	3/8
Left & Right Bullnose Corner	2-3/4 x 5-5/8	3/8
4" x 12" Bullnose	3-3/4 x 11-3/4	3/8
Counter Edge	1-7/8 x 5-3/4	3/8
Counter Edge Outside Corner	1-7/8 x 1-7/8	3/8
Quarter Round	7/8 x 5-3/4	3/8
Quarter Round Outside Corner	7/8 x 7/8	3/8
4" Border	4-7/16 x 11-3/4	3/8
4" Border Corner	4-7/16 x 4-7/16	3/8
6" Border	4-11/16 x 11-3/4	3/8
6" Border Corner	4-11/16 x 4-11/16	3/8



3" x 6" Bullnose
6" side



6" x 3" Bullnose
3" side



4" x 12" Bullnose



3" x 6" Bullnose
Corner Left



3" x 6" Bullnose
Corner Right



2" x 6" Counter Edge &
Outside Corner



1" x 6" Quarter Round
& Outside Corner

Product Performance

Abrasion Wear	>125	ASTM C501
Bond Strength	>200 psi	ASTM C482
Break Strength	>400 lbs.	ASTM C648
Coefficient of Friction (Dry)	>0.8	ASTM C1028-89
Coefficient of Friction (Wet)	>0.6	ASTM C1028-89
Water Absorption	<0.10%	ASTM C373

Recommended Usage

Crossville Porcelain Stone products are recommended for interior walls and floors and exterior walls in both residential and commercial applications.

Care and Maintenance

Regular cleaning is the best way to keep your porcelain stone looking new for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville Porcelain Stone products is available at www.crossvilleinc.com.

Shade & Texture Index

Quartzite has a shade variation of V4



V1



V2



V3



V4

V1=Uniform Appearance
V2=Slight Variation
V3=Moderate Variation
V4=Substantial Variation



Crossville, Inc. • P.O. Box 1168, Crossville, TN 38557
Phone: 931.484.2110 • Fax: 931.456.2956
E-Mail: crossc@crossvilleinc.com
www.crossvilleinc.com



Quartzite
Cream Multicolor AV12 16" x 6", 12" x 12", 12" x 18", 18" x 18"
and 3" x 3" Mosaic