

Weatherstone and Weatherstone XT

PORCELAIN STONE

- Features the appearance and rustic look of natural slate
- Complemented by an extensive selection of trim
- Wood-look border/insert adds a unique design dimension
- Ideal for all types of residential and commercial installations
- The varying body color is an integral part of the tile.



Summer Cloud AV131



Autumn Sun AV132



Taupe Mist AV133



Wetstone AV134



Midnite Storm AV135



3" x 6"
Border/Insert



3" x 3"
Corner/Insert



3" x 6"
Border/Insert



3" x 3"
Corner/Insert



3" x 6"
Border/Insert



3" x 3"
Corner/Insert



3" x 6"
Border/Insert



3" x 3"
Corner/Insert



3" x 6"
Border/Insert



3" x 3"
Corner/Insert



6" x 6" Corner/Insert



6" x 6" Corner/Insert



6" x 6" Corner/Insert



6" x 6" Corner/Insert




6" x 6" Corner/Insert




6" x 12" Border



6" x 12" Border



6" x 12" Border



6" x 12" Border



6" x 12" Border

Size & Trim Data

Surface/Texture	Size Actual	Size	Thickness
UPS	3 x 3"	2-3/4 x 2-3/4	3/8
UPS	3 x 6"	2-3/4 x 5-5/8	3/8
UPS/XT	6 x 6"	5-3/4 x 5-3/4	3/8
UPS/XT	6 x 12"	5-3/4 x 11-3/4	3/8
UPS/XT	12 x 12"	11-3/4 x 11-3/4	3/8
UPS/XT	12 x 18"	11-3/4 x 17-3/4	3/8
UPS/XT	18 x 18"	17-3/4 x 17-3/4	3/8

Coordinating Trim available in UPS finish only:

3" x 6" Bullnose Corner	2-3/4 x 5-3/4	3/8
3" x 6" Bullnose (6" side)	2-3/4 x 5-5/8	3/8
6" x 3" Bullnose (3" side)	5-5/8 x 2-3/4	3/8
4" x 12" Bullnose	3-3/4 x 11-3/4	3/8
6" x 12" Cove Base	5-7/8 x 11-7/8	3/8
3" x 6" Wood Decorative Border/Insert	2-3/4 x 5-5/8	3/8
3" x 3" Wood Decorative Border/Insert	2-3/4 x 2-3/4	3/8
6" x 12" Border	5-3/4 x 11-5/8	3/8
6" x 6" Border Corner	5-3/4 x 5-3/4	3/8




3" x 6" Bullnose
6" Side



6" x 3" Bullnose
3" Side



4" x 12" Bullnose



6" x 12" Cove Base



3" x 6" Bullnose
Corner Left



3" x 6" Bullnose
Corner Right

Recommended Usage

The WeatherStone Series-UPS surface finish is recommended for interior walls, floors and exterior walls. The WeatherStone Series-XT surface finish is suitable for exterior floors and walls only. Crossville Porcelain Stone does not recommend the use of the WeatherStone Series-XT surface finish for interiors. Both WeatherStone Series surface finishes are suitable for both residential and commercial applications.

Product Performance

Abrasive Wear	220-240	ASTM C501
Bond Strength	>200 psi	ASTM C482
Breaking Strength	320-340 lbs.	ASTM C648
Coefficient of Friction		
UPS (Wet & Dry)	>0.6	ASTM C1028-89
XT (Wet & Dry)	>0.8	ASTM C1028-89
Water Absorption	<0.10%	ASTM C373
Facial Dimensions Range	0.30% Max.	ASTM C499
Frost Resistance	Resistant	ASTM C1026
Chemical Resistance	Unaffected	ASTM C650

Care & Maintenance

Regular cleaning is the best way to keep your Weather- Stone tile looking new for years to come. Use clean, hot water for general cleaning and combine with a household cleaner for more aggressive cleaning. Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville Porcelain Stone products is available at www.crossvilleinc.com.

Shade & Texture Index

WeatherStone has a shade variation of V4.



V1



V2



V3



V4

V1=Uniform Appearance
V2=Slight Variation
V3=Moderate Variation
V4=Substantial Variation



CROSSVILLE®
ELEVATE YOUR SPACE

Crossville, Inc. • P.O. Box 1168, Crossville, TN 38557
Phone: 931.484.2110 • Fax: 931.456.2956
E-Mail: crossc@crossvilleinc.com
www.crossvilleinc.com

