

DHURRIE REMIX:

Style Number	DRR
Specifications	
Construction	Patterned Cut/Loop
Yarn Content	Zeftron® Nylon with 25% recycled content
Dye Method	Solution/Space
Machine Gauge	1/8 in. (31.5 col./10 cm.)
Stitch Count	14.6 S.P.I. (57.4/10 cm.)
Finished Pile Thickness	.219 in. (5.56 mm.)
Average Density	6080
Yarn Weight Tufted	38 oz./yd.2 (1288 g./m2)
Primary Backing	Masterline® Woven Primary
Secondary Backing	Woven Polypropylene
Width	12 feet (3.66m.)
Pattern Repeat	6.0" w x 00" l (15.2 cm. x 00 cm.)
Performance	
Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
CRI Green Label Plus	Certification #GLP7078
Warranties	
Zeftron® Stain Warranty	Lifetime Stain Removal – Limited Guarantee
Zeftstat® Warranty	Lifetime Carpet Static Warranty
Zeftwear® Warranty	Lifetime Carpet Wear – Limited Warranty
Zeftron® Certification	Class III, Extra Heavy Traffic
enviro6ix™	Minimum of 25% recycled content
Zeftron® Recycling	6ix Again®
Additional Information	
Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at www.bolyu.com
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

BOLYÜ

Beaulieu Commercial (USA)
201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

Beaulieu Commercial (Canada)
335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075

Carpet Design® 2007 Beaulieu Group, LLC.