

# DHURRIE REMIX TILE:

**Style Number**

DRT

## Specifications

<b>Construction</b>	Patterned Cut/Loop
<b>Yarn Content</b>	Zeftron® Nylon with 25% recycled content
<b>Dye Method</b>	Solution/Space
<b>Machine Gauge</b>	1/8 in. (31.5 col./10 cm.)
<b>Stitch Count</b>	13.6 S.P.I. (54/10 cm.)
<b>Finished Pile Thickness</b>	.22 in. (5.58 mm.)
<b>Average Density</b>	5,809
<b>Yarn Weight Tufted</b>	36 oz./yd.2 (1220 g./m2)
<b>Primary Backing</b>	Non Woven
<b>Secondary Backing</b>	Nexterra® with 85% Post Consumer Recycled Content and Puralex®
<b>Modular Tile Width</b>	24" x 24" (61 cm. x 61 cm.)

## Performance

<b>Static Control</b>	Less Than 3.5 k.v. Step
<b>Flame Resistance</b>	Passes (DOC FF-1-70)
<b>Flooring Radiant Panel</b>	Class 1(ASTM E-648)
<b>Smoke Density</b>	Less Than 450 (ASTM E-662)
<b>CRI Green Label Plus</b>	Certification #GLP8595

## Warranties

<b>Zeftron® Stain Warranty</b>	Lifetime Stain Removal – Limited Guarantee
<b>Zeftstat® Warranty</b>	Lifetime Carpet Static Warranty
<b>Zeftwear® Warranty</b>	Lifetime Carpet Wear – Limited Warranty
<b>Zeftron® Certification</b>	Class III, Extra Heavy Traffic
<b>enviro6ix™</b>	Minimum of 25% recycled content
<b>Zeftron® Recycling</b>	6ix Again®
<b>Edge Ravel</b>	Lifetime Warranty
<b>Delamination</b>	Lifetime Warranty, under normal use
<b>Tuft Bind</b>	Lifetime Warranty

## Additional Information

<b>Custom Colors</b>	Contact Sales Representative
<b>Backing Options</b>	See iLoc® backings at <a href="http://www.bolyu.com">www.bolyu.com</a>
<b>Samples</b>	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



# BOLYÜ

201 Princeton Boulevard  
Adairsville, Georgia 30103  
800 451 1250

335 Roxton Street  
Acton Vale, Quebec  
Canada J0H 1A0  
888 467 5075