

DIRECT EFFECT:

Style Number	DEF
Specifications	
Construction	Cut Pile
Yarn Content	XTI® Nylon
Dye Method	Beck
Machine Gauge	1/10 in. (39.4 col./10 cm)
Stitch Count	12 S.P.I. (47.2/10 cm)
Finished Pile Thickness	.260 in. (6.60 mm)
Average Density	4,985
Pile Height Tufted	.31in. (1.2 mm) high
Yarn Weight Tufted	36 oz./yd.2 (1220 g./m2)
Primary Backing	Masterline® Woven Primary
Secondary Backing	Woven Polypropylene with Post Consumer Recycled Content
Pattern Repeat	Not Applicable
Performance	
Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1(ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP3078
Warranties	
Wear	10 Year Limited Warranty
Additional Information	
Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at www.bolyu.com
Coordinating Styles	Chain of Events, On the Edge & Street Smart
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



B Ō L Y Ü

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075