

Listings & Approvals

Coal Tar Pitch Felt Systems With Hot Roofing Coal Tar Pitch

T. Clear Corp, Hamilton OH 45012

R14358(N)
Class A

Coal Tar Pitch Felt Systems with Hot Roofing Coal Tar Pitch

1. **Deck:** C-15/32 **Incline:** 1
Base Sheet: Required for combustible decks— asphalt organic, asbestos or inorganic glass, nailed.
Ply Sheet: Two or more layers Type 15 asphalt organic, asbestos or type G1 inorganic glass, coal tar pitch or bituman. 25 lbs./sq. sealed with coal tar pitch or bituman. 25 lbs./sq. followed by coal tar at 45 lbs./sq.
Insulation: Dow Chemical Styrofoam RM, PC or Styrorib (plastic) 1 in. minimum with or without attachment.
Scrim: (Optional) “Fabrene”, “International Paper D689” or “Rufon Polypropylene”. 2 oz./sq. yd.
Surfacing: Crushed stone, river bottom stone (3/4 to 1 3/4 in. diameter). 900lbs./sq. concrete blocks, 10 lbs./sq. minimum spread not more than 1/8 in. apart, or LightGuard® panels surfaced with 5/16 in. minimum concrete mortar, butted together.

2. **Deck:** C-15/32 **Incline:** 2
Base Sheet: Required for combustible decks — Type 15 asphalt inorganic felt, nailed.
Ply Sheet: Two or more layers Type 15 asphalt organic, asbestos or Type G1 inorganic glass felt secured with hot roofing asphalt.
Insulation: Dow Chemical Styrofoam RM, PD or Styrorib (plastic) 1 in. minimum.
Scrim: (Optional) “Fabrene”, “International Paper D689” or “Rufon Polypropylene”. 2 oz./sq. yd.
Surfacing: Crushed stone, river bottom stone (3/4 to 1 3/4 in. diameter). 900lbs./sq. concrete blocks, 10 lbs./sq. minimum spread not more than 1/8 in. apart, or LightGuard® panels surfaced with 5/16 in. minimum concrete mortar, butted together.

Underwriter's Laboratories Inc. ®

®LightGuard is a registered trademark of the T. Clear Corporation