



1800 Mastic Product Specifications

PRODUCT DESCRIPTION:

The 1800 Mastic is a single component, hydrocarbon polymer, elastomeric compound.

PURPOSE:

The 1800 Mastic was designed to be used in conjunction with the 1800 Air/Vapor Barrier membrane to fill any cracks or voids in the masonry that will be receiving the membrane.

ADVANTAGES:

- Remains flexible during freeze-thaw cycles
- Ready to use

SPECIFICATIONS:

- Color – Gray
- Consistency – Rubber coating

Property	Test Method	Results
Elongation	ASTM D 412	1,300%
Peel Adhesion	ASTM D 903	28 lbs/inch
Hydrostatic Head Pressure	ASTM D 751	57 ft./max
Pliability @ 25°F	ASTM E 1970	Pass
Solids		58%

PACKAGING:

5 Gallon Buckets

APPROXIMATE USAGE:

Actual coverage rate will vary depending on depth and width of cracks and voids filled.

PREP/APPLICATION:

All surfaces should be free from oil, grease, rust, dirt and any other debris. Apply directly to any surface flaw with a trowel or putty knife.

CLEAN UP:

Use Marflex's Orange 90 cleaner.

PRODUCT HANDLING/STORAGE:

- Do not thin
- Do not use near open flame, sparks or ignition sources
- Avoid breathing solvent fumes
- Avoid prolonged contact with skin
- Keep container closed when not in use
- Unlimited shelf life if properly stored

WARNING/DANGER:

- Use with adequate ventilation
- Keep out of the reach of children
- Do not take internally
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT INDUCE VOMITING

PRODUCT ONLY WARRANTY:

Marflex Building Solutions warrants the product to be of good quality and manufactured to meet published physical properties and quality control standards and will replace or refund the purchase price of this product if proved defective within one year of date of application. This warranty does not apply if there is no working drainage system.

Except as specifically provided herein, Marflex makes no warranty, express, implied or oral including but not limited to any warranty or merchantability, fitness for a particular purpose, usage of trade, course of dealing or course of performance in connection with this agreement. In no event shall Marflex be liable on any such warranty with respect to the product. Marflex shall not be liable for incidental or consequential damages

including, but not limited to damages of the structure, its replacement, contents or personal injury. Some states do not allow limitations on how long an implied warranty lasts or allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

HEALTH AND SAFETY INFORMATION IS GIVEN IN THE MATERIAL SAFETY DATA SHEET AND THE PRODUCT DATA SHEET AVAILABLE FOR THIS PRODUCT. THESE SHOULD BE READ AND UNDERSTOOD BEFORE USING THIS PRODUCT.

Marflex Building Solutions
6866 Chrisman Lane, Middletown, OH 45042
(800) 498-1411 | (513) 422-7285 | Fax – (513) 422-7282
E-mail: technicalsupport@mar-flex.com
Web site: www.MarflexBuildingSolutions.com

07-09.2