

IMAGERY TILE:

Style Number	IMG
Specifications	
Construction	Patterned Loop
Yarn Content	Avalar® X Nylon with Post Industrial Recycled Content
Dye Method	Solution/Space
Machine Gauge	1/12 in. (47.2 col./10 cm.)
Stitch Count	10.6 S.P.I. (41.7/10 cm.)
Finished Pile Thickness	.136 in. (3.45 mm)
Average Density	6,353
Yarn Weight Tufted	24 oz./yd.2 (813.5g./m2)
Primary Backing	Non Woven
Secondary Backing	Nexterra with 85% Post Consumer Recycled Content and Puralex®
Modular Tile Width	24" x 24" (61 cm. x 61 cm.)
Performance	
Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP8595
Warranties	
Wear	Lifetime Limited Warranty
Static	Lifetime Warranty
Edge Ravel	Lifetime Warranty
Delamination	Lifetime Warranty, under normal use
Tuft Bind	Lifetime Warranty
Stain	Lifetime Limited Warranty
Additional Information	
Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at www.bolyu.com
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



B Ō L Y Ü

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075