

# INTRIGUE TILE:

**Style Number**

ITR

## Specifications

<b>Construction</b>	Patterned Loop
<b>Yarn Content</b>	Avalar® X Nylon with Post Industrial Recycled Content
<b>Dye Method</b>	Solution/Space
<b>Machine Gauge</b>	1/12 in. (47.2 col./10 cm.)
<b>Stitch Count</b>	10.6 S.P.I. (41.7/10 cm.)
<b>Finished Pile Thickness</b>	.136 in. (3.45 mm)
<b>Average Density</b>	6,353
<b>Yarn Weight Tufted</b>	24 oz./yd.2 (813.5 g./m2)
<b>Primary Backing</b>	Non Woven
<b>Secondary Backing</b>	Nexterra with 85% Post Consumer Recycled Content and Puralex®
<b>Modular Tile Width</b>	24" x 24" (61 cm. x 61 cm.)

## Performance

<b>Static Control</b>	Less Than 3.5 k.v. Step
<b>Flame Resistance</b>	Passes (DOC FF-1-70)
<b>Flooring Radiant Panel</b>	Class 1 (ASTM E-648)
<b>Smoke Density</b>	Less Than 450 (ASTM E-662)
<b>Soil Resistance</b>	Commercial Anti-Soil Protection
<b>CRI Green Label Plus</b>	Certification #GLP8595

## Warranties

<b>Wear</b>	Lifetime Limited Warranty
<b>Static</b>	Lifetime Warranty
<b>Edge Ravel</b>	Lifetime Warranty
<b>Delamination</b>	Lifetime Warranty, under normal use
<b>Tuft Bind</b>	Lifetime Warranty
<b>Stain</b>	Lifetime Limited Warranty

## Additional Information

<b>Custom Colors</b>	Contact Sales Representative
<b>Backing Options</b>	See iLoc® backings at <a href="http://www.bolyu.com">www.bolyu.com</a>
<b>Samples</b>	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



# B Ō L Y Ü

201 Princeton Boulevard  
Adairsville, Georgia 30103  
800 451 1250

335 Roxton Street  
Acton Vale, Quebec  
Canada J0H 1A0  
888 467 5075