

AT-300 FR

AT-300 FR is a laminated polyester scrim product with taffeta embossed finish. The material is fire retardant and weather resistant with a high tensile strength.

PHYSICAL PROPERTIES AND TYPICAL VALUES

PROPERTY	ASTM TEST METHOD	U.S. VALUE	METRIC VALUE
Weight	D-2103	125 LB/1000 FT ²	61 KG/100 M ²
Thickness	D-2103	25.0 MIL	0.64 MM
Adhesion	5970	20 LBS/2 in.	89 N/5 cm
Tensile	5100	300 LBF	1334 N
Tear Strength	5134	100 LBF	445 N
Cold Impact Strength	D-1709	-20°F	-29°C
Flammability	5903 (Char Length)	4 inches	10 cm

AVAILABLE COLORS

Blue

REEF INDUSTRIES, INC.
The Manufacturing Leader of Specialized Industrial Plastic Films Since 1957.

ARMORLON®

AT-300 FR

PRODUCT INFORMATION • SPECIFICATION GUIDE

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, expressed or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

©2006 REEF INDUSTRIES, INC. Armorlon is a registered trademark of Reef Industries, Inc. 09-06

TOLLFREE 1.800.231.6074

9209 Alameda Genoa Rd. • Houston, Texas 77075

P: 713.507.4251 • F: 713.507.4295

Email: ri@reefindustries.com

