

PIZZAZZ BROADLOOM:

Style Number

PZB

Specifications

Construction

Loop Pattern

Yarn Content

Zeftron® Nylon with 25% Recycled Content

Dye Method

Solution

Machine Gauge

1/12 in. (47.2/10 cm.)

Finished Pile Thickness

.106 in. (2.69 mm)

Average Density

10,188

Stitch Count

13 S.P.I. (51.2/10 cm.)

Yarn Weight Tufted

30 oz./yd.2 (1,017 g./m2)

Primary Backing

Polypropylene

Secondary Backing

iLoc® ES with Post Consumer Recycled Content

Pattern Repeat

24" x 17.5" (61 cm. x 45 cm.)

Performance

Static Control

Less Than 3.5 k.v. Step

Flame Resistance

Passes (DOC FF-1-70)

Flooring Radiant Panel

Class 1 (ASTM E-648)

Smoke Density

Less Than 450 (ASTM E-662)

Soil Resistance

Commercial Anti-Soil Protection

CRI Green Label Plus

Certification #GLP7078

Warranties

Zeftron® Stain Warranty

Lifetime Stain Removal – Limited Guarantee

Zefstat® Warranty

Lifetime Carpet Static Warranty

Zeftwear® Warranty

Lifetime Carpet Wear – Limited Warranty

Zeftron® Certification

Class III, Extra Heavy Traffic

enviro6ix®

Minimum 25% Recycled Content

Zeftron® Recycling

6ix Again®

Delamination

Lifetime of Carpet, under normal use

Tuft Bind

Lifetime of Carpet, not to zipper, wet or dry

Dimensional Stability

Lifetime of Carpet

Additional Information

Custom Colors

Contact Sales Representative

Backing Options

See iLoc® backings at www.bolyu.com

Coordinating Styles

Dazzle & Pizzazz Tile

Samples

800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



BOLYÜ

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075