

PIZZAZZ:

Style Number

PZZ

Specifications

Construction	Loop Pattern
Yarn Content	Zeftron® Nylon with 25% recycled content
Dye Method	Solution
Machine Gauge	1/12 in. (47.2/10 cm.)
Finished Pile Thickness	.118 in. (3.0 mm)
Average Density	8,237
Stitch Count	11.7 S.P.I. (46/10 cm.)
Yarn Weight Tufted	27 oz./yd.2 (915 g./m2)
Primary Backing	Non Woven
Secondary Backing	Nexterra® with 85% Post Consumer Recycled Content with Puralex®
Width	24" x 24" (61 cm. x 61 cm.)
Total Recycled Content	64-67%

Performance

Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1(ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification # GLP8595

Warranties

Zeftron® Nylon	Lifetime Stain Removal – Limited Guarantee
Zeftstat® Warranty	Lifetime Carpet Static Warranty
Zeftwear® Warranty	Lifetime Carpet Wear – Limited Warranty
Zeftron® Certification	Class III, Extra Heavy Traffic
envirobix™	Minimum 25% Recycled Content
Zeftron® Recycling	6ix Again®
Delamination	Lifetime Warranty, under normal use
Tuft Bind	Lifetime Warranty, not to zipper, wet or dry
Dimensional Stability	Lifetime Warranty

Additional Information

Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at www. bolyu.com
Coordinating Styles	Dazzle and Pizzazz broadloom
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



BÖLYÜ

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075