

SOLITUDE:

Style Number

SLT

Specifications

Construction	Pattern Cut/Loop
Yarn Content	Antron® Legacy nylon
Dye Method	75% Solution Dyed, 25% Yarn Dyed
Machine Gauge	1/10 in. (39.4 col./10 cm.)
Stitch Count	14.6 S.P.I. (57.4/10 cm.)
Finished Pile Thickness	.190 in. (4.83 mm.)
Average Density	6,253
Yarn Weight Tufted	36 oz./yd.2 (1220 g./m2)
Primary Backing	Masterline® Woven Primary
Secondary Backing	Woven Polypropylene with Post Consumer Recycled Content
Width	12 feet (3.66m.)
Pattern Repeat	.40" w x .43" l (1.01 cm. x 1.09 cm.)

Performance

Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	DuraTech® Patented Soil Resistance
CRI Green Label Plus	Certification #GLP7078

Warranties

Wear	10 Year Limited Warranty
-------------	--------------------------

Additional Information

Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at www.bolyu.com
Coordinating Styles	Multiple
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



B Ō L Y Ü

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075