

TECHNICAL DATA

Dry As a Bone™



DĒCO PRODUCTS, INC.

DĒCO ULTRA THERM

DESCRIPTION

DĒCO ULTRA THERM is specially formulated for exterior or interior reflective coating used on vertical or horizontal surfaces. DĒCO ULTRA THERM is an acrylic emulsion fluid with ceramic insulating properties that forms a seamless waterproof membrane over concrete, *masonry block*, metal or wood.

USE:

Provides maximum insulating and waterproofing performance when used according to application instructions.

WARRANTY

DĒCO ULTRA THERM is warranted to perform as specified for 7 years from date of application.

B E N E F I T S

- Insulated coating
- VOC compliant
- Non-toxic - Non-caustic - Non-flammable
- Crack resistant
- UV protected
- 100% elasticity
- Retards oil and grease
- Eliminates bacteria growth and mildew
- No color fading
- Can be applied to damp or dry walls
- Standard color: White / Can be tinted to pastel colors
- Only one application required
- Airless sprayer applied
- 5 gallon packaging



Made in the U.S.A.



For more information contact:
DĒCO Products, Inc.
7900 E. 40th Ave.
Denver, CO 80207
(800) 500-3326 Fax (303) 316-9371
e-mail: deco20seal@aol.com



S P E C I F I C A T I O N D A T A

TEST DATA:

DĒCO ULTRA THERM meets and or exceeds the following ASTM tests:

ASTMD 2939 Section 15 Resistance to water

ASTMD 466-42 Resistance to water action.

ASTME 96 Water vapor transmission.

ICBO AC29 Section 4.4.4.3 and 4.4.4.5 Hydrostatic Pressure Test

ASTMC 836-95 Section 5.7 Hydrostatic Crack Bridging Pressure Test

ASTMD 2665-1999 Color Fastness Of Surface Coating

ASTM D 3273-94 Resistance to Mold Growth of Surface Coating

LIMITATIONS:

Do not let product freeze. Store indoors at temperatures above 34 degrees Fahrenheit. Do not store in direct sun light. The temperature must be 38 degrees Fahrenheit and rising before application. Maximum application temperature not to exceed 90 degrees Fahrenheit. Do not dilute DĒCO ULTRA THERM. Do not apply DĒCO ULTRA THERM when the threat of rain is imminent.

KEEP OUT OF REACH OF CHILDREN

INSTALLATION:

Preparation:

Prior cleaning may be required to dislodge all loose material.

Remove all efflorescence, dirt, grease, oils and other foreign material from the surface which is to be coated. Repair all structural deficiencies. After preparation of surface, apply DĒCO 20 (on masonry substrates only) as a base sealant before DĒCO ULTRA THERM.

(SEE SPECIFICATION DATA ON DĒCO 20)

Wood and metal surfaces may require a primer before application of DĒCO ULTRA THERM.

Cover all areas or surfaces not to be sealed, such as doors, windows and floors, prior to applying DĒCO 20. Use caution when applying on windy days. If DĒCO 20 comes in contact with glass, clean immediately with water. Over-spray can cause etching of glass.

Installation:

NOTE: Always perform a job site test to insure desired results.

Coverage: Approximately 80 square feet per gallon depending upon the porosity of the substrate.

Application of DĒCO ULTRA THERM:

After DĒCO 20 (only when used with masonry substrates) has dried, apply DĒCO ULTRA THERM without dilution. Thickness of application will be determined by porosity, density and stability of substrate to be treated. 20 mils wet will dry to approximately 14 mils. Two coats are typically required to get 20 mil wet.

WARRANTY:

DĒCO ULTRA THERM is warranted to perform as specified for a period of not less than 7 years from date of application. DĒCO Products, Inc. warrants its product to be good quality and will replace or refund the purchase price of any products proved defective. It is the responsibility of the buyer to determine that this product meets their needs and to apply it properly. The application of DĒCO ULTRA THERM requires that the installer be skilled in achieving results from applying this product. Satisfactory results depend not only upon quality product, but also upon many factors beyond DĒCO Products, Inc.'s control. DĒCO Products, Inc. makes no warranty or guarantee, expressed or implied, including warranty of fitness or merchantability, respecting its products. DĒCO Products, Inc. shall have no other liability with respect thereto. Guarantee of this product, DĒCO ULTRA THERM, when used according to directions, is limited to refund of purchase price or replacement of product, if it is proved defective. DĒCO Products, Inc. shall not be liable for cost of labor, direct or incidental consequential damages.

TECHNICAL SERVICES:

Technical advice furnished by DĒCO Products, Inc., concerning any use or application of DĒCO ULTRA THERM is reliable as current technology allows. DĒCO Products, Inc. makes no warranty, expressed or implied, of any use of application for which such advise is furnished.

DISTRIBUTOR:

DĒCO ULTRA THERM

DĒCO Products, Inc.

7900 E. 40th Ave.

Denver, Colorado 80207 USA

(800) 500-3326
