

ZOOM:

Style Number	ZOM
Specifications	
Construction	Textured Loop Pattern
Yarn Content	Avalar® X Nylon with Recycled Content and Puralex®
Dye Method	Solution / Space
Machine Gauge	1/10 in. (39.4 col./10 cm)
Stitch Count	13 S.P.I. (51.2/10 cm)
Finished Pile Thickness	.144 in. (3.66 mm)
Average Density	7,500
Yarn Weight Tufted	30 oz./yd.2 (1017 g./m2)
Primary Backing	Masterline® Woven Primary
Secondary Backing	Woven Polypropylene with Post Consumer Recycled Content
Pattern Repeat	.80" w x .46" l (2.0 cm. x 3.3 cm.)
Performance	
Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP7078
Warranties	
Wear	10 Year Limited Warranty
Additional Information	
Custom Colors	Contact Mill Representative
Coordinating Styles	Reaction II
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



B Ō L Y Ü

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075