

## SPECIFICATIONS

|                                |                                                            |
|--------------------------------|------------------------------------------------------------|
| <b>Construction</b>            | Textured Loop Pattern                                      |
| <b>Yarn Content</b>            | Avalar® X Nylon with Puralex®                              |
| <b>Dye Method</b>              | Solution / Space Dyed                                      |
| <b>Machine Gauge</b>           | 1/10 in (39.4 in./10 cm.)                                  |
| <b>Stitch Count</b>            | 11 S.P.I (43.3/ 10 cm.)                                    |
| <b>Finished Pile Thickness</b> | .116 in. (2.94 mm.)                                        |
| <b>Average Density</b>         | 7,262                                                      |
| <b>Yarn Weight Tufted</b>      | 26 oz. /yd. <sup>2</sup> (881 g./m. <sup>2</sup> )         |
| <b>Primary Backing</b>         | Masterline® Woven Primary                                  |
| <b>Secondary Backing</b>       | Woven Polypropylene with<br>Post Consumer Recycled Content |
| <b>Width</b>                   | 12 feet (3.66 m.)                                          |
| <b>Pattern Repeat</b>          | .60" w x 1.8" l (1.5 cm. x 4.6 cm.)                        |
| <b>Total Recycled Content</b>  | 2.58%                                                      |

## PERFORMANCE

|                               |                                 |
|-------------------------------|---------------------------------|
| <b>Static Control</b>         | Less Than 3.5 K.V. Step         |
| <b>Flame Resistance</b>       | Passes (DOC FF-1-70)            |
| <b>Flooring Radiant Panel</b> | Class 1 (ASTM E-648)            |
| <b>Smoke Density</b>          | Less than 450 (ASTM E-662)      |
| <b>Soil Resistance</b>        | Commercial Anti-Soil Protection |
| <b>CRI Green Label Plus</b>   | Certification # GLP7078         |

## WARRANTIES

|               |                           |
|---------------|---------------------------|
| <b>Wear</b>   | Ten Year Limited Warranty |
| <b>Static</b> | Lifetime Warranty         |
| <b>Stain</b>  | Lifetime Limited Warranty |

## ADDITIONAL INFORMATION

|                            |                                                                                                                 |
|----------------------------|-----------------------------------------------------------------------------------------------------------------|
| <b>Custom Colors</b>       | Contact Sales Representative                                                                                    |
| <b>Backing Options</b>     | See iLoc® backings at<br><a href="http://www.cambridgecarpet.com">www.cambridgecarpet.com</a>                   |
| <b>Additives</b>           | Puralex® is a refresher that is<br>environmentally friendly and specially<br>formulated to help purify the air. |
| <b>Coordinating Styles</b> | Aviator, Inventor and Pioneer                                                                                   |
| <b>Samples</b>             | 800 451 1250                                                                                                    |



Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

## FOUNDER 2.0

style # 6FDR

# Cambridge®

201 Princeton Boulevard  
P.O. Box 1110  
Adairsville, GA 30103  
800 451 1250

335 Roxton Street  
Acton Vale, Quebec  
Canada JOH 1A0  
888 467 5075

[www.cambridgecarpet.com](http://www.cambridgecarpet.com)

A Beaulieu Commercial Brand