SPECIFICATIONS

Construction Textured Loop Pattern

Yarn Content Cambridge Approved / BCF Nylon

Dye MethodSolution / SpaceMachine Gauge1/10 in (39.4 in./10 cm.)Stitch Count12.7 S.P.I (49.9/ 10 cm.)

Finished Pile Thickness .160 in. **Average Density** 6,300

Yarn Weight Tufted 28 oz. /yd.² (949 g./m.²)
Primary Backing Masterline® Woven Primary
Secondary Backing Woven Polypropylene

Width 12 feet (3.66 m.)

Pattern Repeat .60" w x .63" I (1.5 cm. x 1.6 cm.)

Total Recycled Content 2.50%

PERFORMANCE

Static Control
Flame Resistance
Flooring Radiant Panel
Smoke Density
Soil Resistance
CRI Green Label Plus

Less Than 3.5 K.V. Step
Passes (DOC FF-1-70)
Class 1 (ASTM E-648)
Less than 450 (ASTM E-662)
Commercial Anti-Soil Protection
Certification # GLP7078

WARRANTIES

Wear 10 Year Limited Warranty

ADDITIONAL INFORMATION

Custom Colors Backing Options

Coordinating Styles Samples

Contact Sales Representative See iLoc[®] backings at www.cambridgecarpet.com Aviator, Founder & Pioneer





800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

Carpet Design® 2003 Beaulieu Group, LLC.

INVENTOR

style # 6351



201 Princeton Boulevard P.O. Box 1110 Adairsville, GA 30103 800 451 1250

335 Roxton Street Acton Vale, Quebec Canada JOH 1A0 888 467 5075

www.cambridgecarpet.com

A Beaulieu Commercial Brand