

SPECIFICATIONS

Construction	Interloop Pattern
Yarn Content	Avalar [®] X Nylon with Puralex [®]
Dye Method	Solution / Space Dyed
Machine Gauge	1/12 in (47.2 in./10 cm.)
Stitch Count	9.3 S.P.I (36.7/ 10 cm.)
Finished Pile Thickness	.122 in. (3.10 mm)
Average Density	7,082
Yarn Weight Tufted	24 oz. /yd. ² (813 g./m. ²)
Primary Backing	Nonwoven
Secondary Backing	Nexterra [®] with 85% Post Consumer Recycled Content
Modular Tile Width	24" x 24" (61 cm. x 61cm.)
Total Recycled Content	62%

PERFORMANCE

Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification # GLP8595

WARRANTIES

Wear	Lifetime Limited Warranty
Static	Lifetime Warranty
Tuft Bind	Lifetime Warranty
Edge Ravel	Lifetime Warranty
Zippering	Lifetime Warranty, not to zipper wet or dry
Pilling & Fuzzing	Lifetime Warranty
Delamination	Lifetime Warranty, under normal use
Dimensional Stability	Lifetime Warranty

ADDITIONAL INFORMATION

Custom Colors	Contact Sales Representative
Backing Options	See iLoc [®] folder for additional options
Additives	Puralex [®] is a refresher that is environmentally friendly and specially formulated to help purify the air.
Samples	800 451 1250



Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

Carpet Design[®] 2005 Beaulieu Group, LLC.

PRODUCER TILE

style # 6TPRD

Cambridge[®]

201 Princeton Boulevard
P.O. Box 1110
Adairsville, GA 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada JOH 1A0
888 467 5075

www.cambridgecarpet.com

A Beaulieu Commercial Brand