

SPECIFICATIONS

Construction	Patterned Scroll
Yarn Content	Avalar® SDX Nylon with 25% Recycled Content and Puralex®
Dye Method	Solution Dyed
Machine Gauge	1/12 in (47.2 in./10 cm.)
Stitch Count	10 S.P.I (39.4/ 10 cm.)
Finished Pile Thickness	.116 in. (2.95 mm)
Average Density	7,759
Yarn Weight Tufted	25 oz. /yd. ² (847 g./m. ²)
Primary Backing	Non Woven
Secondary Backing	Nexterra® with 85% Post Consumer Recycled Content
Modular Tile Width	24" x 24" (61 cm. x 61cm.)
Total Recycled Content	61 – 65%

PERFORMANCE

Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification # GLP8595

WARRANTIES

Wear	Lifetime Limited Warranty
Static	Lifetime Warranty
Tuft Bind	Lifetime Warranty
Edge Ravel	Lifetime Warranty
Zippering	Lifetime Warranty, not to zipper wet or dry
Pilling & Fuzzing	Lifetime Warranty
Delamination	Lifetime Warranty, under normal use
Dimensional Stability	Lifetime Warranty

ADDITIONAL INFORMATION

Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at www.cambridgecarpet.com

Additives	Puralex® is a refresher that is environmentally friendly and specially formulated to help purify the air.
------------------	---

Samples	800 451 1250
----------------	--------------



Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

Carpet Design® 2008 Beaulieu Group, LLC.

TRAPEZE

style # 6TTPZ

Cambridge®

201 Princeton Boulevard
P.O. Box 1110
Adairsville, GA 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada JOH 1A0
888 467 5075

www.cambridgecarpet.com

A Beaulieu Commercial Brand