

## SPECIFICATIONS

<b>Construction</b>	Textured Loop Pattern
<b>Yarn Content</b>	Cambridge Approved Nylon with 25% Post Industrial Recycled Content
<b>Dye Method</b>	Solution
<b>Machine Gauge</b>	1/10 in (39.4 in./10cm)
<b>Stitch Count</b>	9 S.P.I (31.5/ 10cm)
<b>Finished Pile Thickness</b>	.109 in. (2.77mm)
<b>Average Density</b>	7,266
<b>Yarn Weight Tufted</b>	22 oz. /yd. <sup>2</sup> (746 g/m <sup>2</sup> )
<b>Primary Backing</b>	Non Woven
<b>Secondary Backing</b>	Nexterra <sup>®</sup>
<b>Width</b>	24" x 24" (61cm x 61cm)
<b>Total Recycled Content</b>	63%

## PERFORMANCE

<b>Static Control</b>	Less Than 3.5 K.V. Step
<b>Flame Resistance</b>	Passes (DOC FF-1-70)
<b>Flooring Radiant Panel</b>	Class 1 (ASTM E-648)
<b>Smoke Density</b>	Less than 450 (ASTM E-662)
<b>Soil Resistance</b>	Commercial Anti-Soil Protection
<b>CRI Green Label</b>	Certification # GLP8595

## WARRANTIES

<b>Wear</b>	Lifetime Limited Warranty
<b>Static</b>	Lifetime Warranty
<b>Tuft Bind</b>	Lifetime Warranty
<b>Edge Ravel</b>	Lifetime Warranty
<b>Zippering</b>	Lifetime Warranty, not to zipper wet or dry
<b>Pilling &amp; Fuzzing</b>	Lifetime Warranty
<b>Delamination</b>	Lifetime Warranty, under normal use
<b>Dimensional Stability</b>	Lifetime Warranty

## ADDITIONAL INFORMATION

<b>Custom Colors</b>	Contact Sales Representative
<b>Backing Options</b>	See iLoc <sup>®</sup> backings at <a href="http://www.cambridgecarpet.com">www.cambridgecarpet.com</a>
<b>Coordinating Styles Samples</b>	Multiple 800 451 1250



Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

WYNFORD III  
TILE  
style # 6WYNT

# Cambridge<sup>®</sup>

201 Princeton Boulevard  
P.O. Box 1110  
Adairsville, GA 30103  
800 451 1250

335 Roxton Street  
Acton Vale, Quebec  
Canada JOH 1A0  
888 467 5075

## SPECIFICATIONS

<b>Construction</b>	Textured Loop Pattern
<b>Yarn Content</b>	Cambridge Approved Nylon
<b>Dye Method</b>	Solution
<b>Machine Gauge</b>	1/10 in (39.4 in./10 cm.)
<b>Stitch Count</b>	8 S.P.I (31.5 in./ 10 cm.)
<b>Finished Pile Thickness</b>	.135 in. (3.42 mm.)
<b>Average Density</b>	6,933
<b>Yarn Weight Tufted</b>	26 oz. /yd. <sup>2</sup> (881.3 g./m <sup>2</sup> )
<b>Primary Backing</b>	Polypropylene
<b>Secondary Backing</b>	Woven Polypropylene with Post Consumer Recycled Content
<b>Width</b>	12 feet (3.66 m.)
<b>Pattern Repeat</b>	None
<b>Total Recycled Content</b>	2.58%

## PERFORMANCE

<b>Static Control</b>	Less Than 3.5 K.V. Step
<b>Flame Resistance</b>	Passes (DOC FF-1-70)
<b>Flooring Radiant Panel</b>	Class 1 (ASTM E-648)
<b>Smoke Density</b>	Less than 450 (ASTM E-662)
<b>Soil Resistance</b>	Commercial Anti-Soil Protection
<b>CRI Green Label</b>	Certification # GLP7078

## WARRANTIES

<b>Wear</b>	10 Year Limited Warranty
-------------	--------------------------

## ADDITIONAL INFORMATION

<b>Custom Colors</b>	Contact Sales Representative
<b>Backing Options</b>	See iLoc <sup>®</sup> backings at <a href="http://www.cambridgecarpet.com">www.cambridgecarpet.com</a>
<b>Coordinating Styles</b>	Multiple
<b>Samples</b>	800 451 1250



Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

Carpet Design<sup>®</sup> 2005 Beaulieu Group, LLC.

WYNFORD III

style # 6258

# Cambridge<sup>®</sup>

201 Princeton Boulevard  
P.O. Box 1110  
Adairsville, GA 30103  
800 451 1250

335 Roxton Street  
Acton Vale, Quebec  
Canada JOH 1A0  
888 467 5075

[www.cambridgecarpet.com](http://www.cambridgecarpet.com)

A Beaulieu Commercial Brand