

BISCAYNE

SPECIFICATIONS

Style Number	9BSC
Construction	Tip Sheared Loop Pattern
Yarn Content	Aqua Approved SD Nylon
Dye Method	Solution
Machine Gauge	1/10 in. (39.4 col./10 cm.)
Stitch Count	12.7 S.P.I. (50/10 cm.)
Finished Pile Thickness	.171 in. (4.34 mm.)
Average Density	6,736
Yarn Weight Tufted	32 oz./yd.2 (1084 g./m2)
Primary Backing	Polypropylene
Secondary Backing	Woven Polypropylene with Post Consumer Recycled Content
Width	12 feet (3.66m.)
Pattern Repeat	.80" w x .88" l (2.0 cm. x 2.2 cm.)
Total Recycled Content	2.36%

PERFORMANCE

Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP7078

WARRANTIES

Wear	10 Year Limited Warranty
------	--------------------------

ADDITIONAL INFORMATION

Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at aquahospitalitycarpets.com
Samples	800 451 1250



201 Princeton Blvd.
P.O. Box 1110
Adairsville, GA 30103

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
(888) 467-5075

Aqua
HOSPITALITY CARPETS

Specifications are based on averages from manufacturing processes and may vary within normal industry Tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance

A Beaulieu Commercial Brand