CYPRESS

SPECIFICATIONS

Style Number 9CPS

Construction Tip Sheared Loop Pattern

Yarn Content Avalar® SD Nylon

Dye Method Solution

 Machine Gauge
 1/10 in. (39.4 col./10 cm.)

 Stitch Count
 12.7 S.P.I. (50/10 cm.)

Finished Pile Thickness .190 in. (4.8 mm.)

Average Density 5,874

Yarn Weight Tufted 32 oz./yd.2 (1084 g./m2)

Primary Backing Polypropylene

Secondary Backing Woven Polypropylene with

Post Consumer Recycled Content

Width 12 feet (3.66m.)

Pattern Repeat .40" w x .50" I (1.0 cm. x 1.3 cm.)

Total Recycled Content 2.36%

PERFORMANCE

Static ControlLess Than 3.5 k.v. StepFlame ResistancePasses (DOC FF-1-70)Flooring Radiant PanelClass 1(ASTM E-648)

Smoke Density
Less Than 450 (ASTM E-662)
Soil Resistance
Commercial Anti-Soil Protection

CRI Green Label Plus Certification #GLP7078

WARRANTIES

Wear

Stain

Lifetime Limited Stain Warranty

Static

Colorfastness

Lifetime Limited Static Control

Lifetime Limited Against Light &

Atmospheric Contaminants

ADDITIONAL INFORMATION

Custom ColorsContact Mill RepresentativeBacking OptionsSee iLoc® backings at

aquahospitalitycarpets.com

Samples 800 451 1250





201 Princeton Blvd. P.O. Box 1110 Adairsville. GA 30103 335 Roxton Street Acton Vale, Quebec Canada J0H 1AQ (888) 467-5075

