## ORTOFINC

## **SPECIFICATIONS**

**Style Number** 9PFN

Construction Tip Sheared Loop Pattern

**Yarn Content** Avalar® SD Nylon

**Dye Method** Solution

Machine Gauge 1/10 in. (39.4 col./10 cm.) Stitch Count 14 S.P.I. (55.1/10 cm.)

**Finished Pile Thickness** .190 in. (4.83 mm)

**Average Density** 5,797

Yarn Weight Tufted 32 oz./yd.2 (1085 g./m2)

**Primary Backing** Polypropylene

**Secondary Backing** Woven Polypropylene with

Post Consumer Recycled Content

Width 12 feet (3.66m.)

**Pattern Repeat** 1.2" w x .85" I (3.05 cm. x 2.16 cm.)

**Total Recycled Content** 2.36%

**PERFORMANCE** 

**Static Control** Less Than 3.5 k.v. Step Flame Resistance Passes (DOC FF-1-70) Flooring Radiant Panel Class 1(ASTM E-648)

**Smoke Density** Less Than 450 (ASTM E-662) Soil Resistance Commercial Anti-Soil Protection

**CRI Green Label Plus** Certification #GLP7078

WARRANTIES

Wear 10 Year Limited

Stain Lifetime Limited Stain Removal **Static** Lifetime Limited Static Control Colorfastness Lifetime Limited Against Light &

**Atmospheric Contaminants** 

ADDITIONAL INFORMATION

**Custom Colors Contact Sales Representative** 

**Backing Options** See iLoc® backings at

aquahospitalitycarpets.com

800 451 1250 Samples





201 Princeton Blvd. P.O. Box 1110 Adairsville, GA 30103 335 Roxton Street Acton Vale, Quebec Canada J0H 1AQ (888) 467-5075

